# MULTI-STANDARD SC 2.1

USA: UL-listed (MTW), Canada: CSA (TEW), Europe: <HAR> H07V-K (depending on cross s.), tin-coated strands

Lapp Kabel® MULTI-STANDARD SC 2.1, power and control cable, PVC single core for field wiring, UL MTW VW-1, UL AWM style 1015 600 V, CSA TEW FT1, HAR H07V-K

**Info**
The all-rounder for many markets
CPR: Article number choice under www.lappkabel.com/cpr

Oil-resistant

**Benefits**
For use in the most important global markets
Reduction in technical documentation
Easier storage; increases the cost-effectiveness of the production process
Works with "Conductor end sleeves XL, insulated"

**Application range**
Factory wiring
Field wiring
Internal wiring of devices
Control cabinet wiring

**Product features**
Flame-retardant according IEC 60332-1-2
Flame-retardant according to UL VW1/CSA FT1
Oil-resistant

**Norm references / Approvals**
Multi-standard cables have conductor strands with nominal sizes in mm² or AWG/kcmil. The master size is mentioned in the table below, while the equivalent size of the other system can be found in the Appendix T16 of this catalogue. For this related


©2021 Lapp Group - Technical changes reserved

# MULTI-STANDARD SC 2.1

secondary size the cross-section of the conductor mostly works out to be greater than the specified nominal value.
Cable type certifications: <HAR> H07V-K acc. EN 50525-2-31, UL AWM style 1015 (by UL acc. UL standard UL 758, U.I. Lapp GmbH's UL AWM file number: E63634), (UL) MTW (by UL acc. UL standard UL 1063, U.I. Lapp GmbH's (UL) MTW file number: E198296), CSA TEW (by CSA acc. CSA standard CSA C22.2 No. 127, CSA class 5835-01)

## Product Make-up

Fine-wire strand made of tinned-copper wires
Special PVC-based core insulation

## Technical Data

| | |
|---|---|
| Classification ETIM 5: | ETIM 5.0 Class-ID: EC000993<br>ETIM 5.0 Class-Description: Single core cable |
| Classification ETIM 6: | ETIM 6.0 Class-ID: EC000993<br>ETIM 6.0 Class-Description: Single core cable |
| Conductor stranding: | Fine wire according to VDE 0295 Class 5/ IEC 60228 Class 5 |
| Minimum bending radius: | OD ≤ 8 mm: 4 x OD*/2 x OD**;<br>8 < OD ≤ 12 mm: 5 x OD*/3 x OD**;<br>OD > 12 mm: 6 x OD*/4 x OD** |
| Nominal voltage: | HAR / IEC: U0/U: 450/750 V;<br>UL (AWM): U: 600 V;<br>UL (MTW): U: 600 V;<br>CSA (TEW): U: 600 V |
| Temperature range: | Fixed installation:<br>HAR/IEC: -40 °C to +70 °C;<br>UL (AWM): up to +105 °C;<br>UL (MTW): up to +90 °C;<br>CSA (TEW): up to +105 °C |

## Note

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.
Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.
Packaging size: Coil ≤ 30 kg, otherwise drum
Photographs and graphics are not to scale and do not represent detailed images of the respective products.
Prices are net prices without VAT and surcharges. Sale to business customers only.
Non-harmonised, nominal cross-sections: 0.5 mm², 0.75 mm², 1 mm², 16 mm²
*for conventional use, **for careful bending; "OD" = outer diameter
The outer diameters stated in the part number table are maximum values.


©2021 Lapp Group - Technical changes reserved

LAPP

PRODUCT INFORMATION

# MULTI-STANDARD SC 2.1

| Article number | Core colour | Conductor cross-section (mm²) | Outer diameter [mm] | m/ring | m/box | Copper index (kg/km) | Weight (kg/km) |
|---|---|---|---|---|---|---|---|
| 4160100 | green/yellow | 0.5 | 2.7 | 100 | - | 4.8 | 11 |
| 4160111 | green | 0.5 | 2.7 | 100 | - | 4.8 | 11 |
| 4160103 | brown | 0.5 | 2.7 | 100 | - | 4.8 | 11 |
| 4160103K | brown | 0.5 | 2.7 | - | 3000 | 4.8 | 11 |
| 4160101 | black | 0.5 | 2.7 | 100 | - | 4.8 | 11 |
| 4160101K | black | 0.5 | 2.7 | - | 3000 | 4.8 | 11 |
| 4160106 | grey | 0.5 | 2.7 | 100 | - | 4.8 | 11 |
| 4160106K | grey | 0.5 | 2.7 | - | 3000 | 4.8 | 11 |
| 4160102 | blue | 0.5 | 2.7 | 100 | - | 4.8 | 11 |
| 4160102K | blue | 0.5 | 2.7 | - | 3000 | 4.8 | 11 |
| 4160114 | dark blue | 0.5 | 2.7 | 100 | - | 4.8 | 11 |
| 4160114K | dark blue | 0.5 | 2.7 | - | 3000 | 4.8 | 11 |
| 4160109 | orange | 0.5 | 2.7 | 100 | - | 4.8 | 11 |
| 4160109K | orange | 0.5 | 2.7 | - | 3000 | 4.8 | 11 |
| 4160107 | violet | 0.5 | 2.7 | 100 | - | 4.8 | 11 |
| 4160107K | violet | 0.5 | 2.7 | - | 3000 | 4.8 | 11 |
| 4160110 | yellow | 0.5 | 2.7 | 100 | - | 4.8 | 11 |
| 4160105 | white | 0.5 | 2.7 | 100 | - | 4.8 | 11 |
| 4160105K | white | 0.5 | 2.7 | - | 3000 | 4.8 | 11 |
| 4160104 | red | 0.5 | 2.7 | 100 | - | 4.8 | 11 |
| 4160104K | red | 0.5 | 2.7 | - | 3000 | 4.8 | 11 |
| 4160108 | pink | 0.5 | 2.7 | 100 | - | 4.8 | 11 |
| 4160126 | blue/white | 0.5 | 2.7 | 100 | - | 4.8 | 11 |
| 4160144 | white/blue | 0.5 | 2.7 | 100 | - | 4.8 | 11 |
| 4160144K | white/blue | 0.5 | 2.7 | - | 3000 | 4.8 | 11 |
| 4160200 | green/yellow | 0.75 | 2.9 | 100 | - | 7.2 | 14 |
| 4160200K | green/yellow | 0.75 | 2.9 | - | 2500 | 7.2 | 14 |
| 4160211 | green | 0.75 | 2.9 | 100 | - | 7.2 | 14 |
| 4160203 | brown | 0.75 | 2.9 | 100 | - | 7.2 | 14 |
| 4160203K | brown | 0.75 | 2.9 | - | 2500 | 7.2 | 14 |
| 4160201 | black | 0.75 | 2.9 | 100 | - | 7.2 | 14 |
| 4160201K | black | 0.75 | 2.9 | - | 2500 | 7.2 | 14 |
| 4160206 | grey | 0.75 | 2.9 | 100 | - | 7.2 | 14 |
| 4160206K | grey | 0.75 | 2.9 | - | 2500 | 7.2 | 14 |

Last Update (05.05.2021)
©2021 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.

LAPP

# MULTI-STANDARD SC 2.1

PRODUCT INFORMATION

| Article number | Core colour | Conductor cross-section (mm²) | Outer diameter [mm] | m/ring | m/box | Copper index (kg/km) | Weight (kg/km) |
|---|---|---|---|---|---|---|---|
| 4160202 | blue | 0.75 | 2.9 | 100 | - | 7.2 | 14 |
| 4160202K | blue | 0.75 | 2.9 | - | 2500 | 7.2 | 14 |
| 4160214 | dark blue | 0.75 | 2.9 | 100 | - | 7.2 | 14 |
| 4160214K | dark blue | 0.75 | 2.9 | - | 2500 | 7.2 | 14 |
| 4160209 | orange | 0.75 | 2.9 | 100 | - | 7.2 | 14 |
| 4160209K | orange | 0.75 | 2.9 | - | 2500 | 7.2 | 14 |
| 4160207 | violet | 0.75 | 2.9 | 100 | - | 7.2 | 14 |
| 4160207K | violet | 0.75 | 2.9 | - | 2500 | 7.2 | 14 |
| 4160210 | yellow | 0.75 | 2.9 | 100 | - | 7.2 | 14 |
| 4160205 | white | 0.75 | 2.9 | 100 | - | 7.2 | 14 |
| 4160205K | white | 0.75 | 2.9 | - | 2500 | 7.2 | 14 |
| 4160204 | red | 0.75 | 2.9 | 100 | - | 7.2 | 14 |
| 4160208 | pink | 0.75 | 2.9 | 100 | - | 7.2 | 14 |
| 4160226 | blue/white | 0.75 | 2.9 | 100 | - | 7.2 | 14 |
| 4160226K | blue/white | 0.75 | 2.9 | - | 2500 | 7.2 | 14 |
| 4160244 | white/blue | 0.75 | 2.9 | 100 | - | 7.2 | 14 |
| 4160244K | white/blue | 0.75 | 2.9 | - | 2500 | 7.2 | 14 |
| 4160300 | green/yellow | 1 | 3.1 | 100 | - | 9.6 | 16 |
| 4160300K | green/yellow | 1 | 3.1 | - | 2000 | 9.6 | 16 |
| 4160311 | green | 1 | 3.1 | 100 | - | 9.6 | 16 |
| 4160303 | brown | 1 | 3.1 | 100 | - | 9.6 | 16 |
| 4160303K | brown | 1 | 3.1 | - | 2000 | 9.6 | 16 |
| 4160301 | black | 1 | 3.1 | 100 | - | 9.6 | 16 |
| 4160301K | black | 1 | 3.1 | - | 2000 | 9.6 | 16 |
| 4160306 | grey | 1 | 3.1 | 100 | - | 9.6 | 16 |
| 4160306K | grey | 1 | 3.1 | - | 2000 | 9.6 | 16 |
| 4160302 | blue | 1 | 3.1 | 100 | - | 9.6 | 16 |
| 4160302K | blue | 1 | 3.1 | - | 2000 | 9.6 | 16 |
| 4160314 | dark blue | 1 | 3.1 | 100 | - | 9.6 | 16 |
| 4160314K | dark blue | 1 | 3.1 | - | 2000 | 9.6 | 16 |
| 4160309 | orange | 1 | 3.1 | 100 | - | 9.6 | 16 |
| 4160309K | orange | 1 | 3.1 | - | 2000 | 9.6 | 16 |
| 4160307 | violet | 1 | 3.1 | 100 | - | 9.6 | 16 |
| 4160310 | yellow | 1 | 3.1 | 100 | - | 9.6 | 16 |
| | | | | | | | |

Last Update (05.05.2021)
©2021 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16

LAPP

PRODUCT INFORMATION

# MULTI-STANDARD SC 2.1

| Article number | Core colour | Conductor cross-section (mm²) | Outer diameter [mm] | m/ring | m/box | Copper index (kg/km) | Weight (kg/km) |
|---|---|---|---|---|---|---|---|
| 4160310K | yellow | 1 | 3.1 | - | 2000 | 9.6 | 16 |
| 4160305 | white | 1 | 3.1 | 100 | - | 9.6 | 16 |
| 4160305K | white | 1 | 3.1 | - | 2000 | 9.6 | 16 |
| 4160304 | red | 1 | 3.1 | 100 | - | 9.6 | 16 |
| 4160304K | red | 1 | 3.1 | - | 2000 | 9.6 | 16 |
| 4160308 | pink | 1 | 3.1 | 100 | - | 9.6 | 16 |
| 4160326 | blue/white | 1 | 3.1 | 100 | - | 9.6 | 16 |
| 4160326K | blue/white | 1 | 3.1 | - | 2000 | 9.6 | 16 |
| 4160344 | white/blue | 1 | 3.1 | 100 | - | 9.6 | 16 |
| 4160344K | white/blue | 1 | 3.1 | - | 2000 | 9.6 | 16 |
| 4160400 | green/yellow | 1.5 | 3.4 | 100 | - | 14.4 | 22 |
| 4160400K | green/yellow | 1.5 | 3.4 | - | 1500 | 14.4 | 22 |
| 4160411 | green | 1.5 | 3.4 | 100 | - | 14.4 | 22 |
| 4160403 | brown | 1.5 | 3.4 | 100 | - | 14.4 | 22 |
| 4160403K | brown | 1.5 | 3.4 | - | 1500 | 14.4 | 22 |
| 4160401 | black | 1.5 | 3.4 | 100 | - | 14.4 | 22 |
| 4160401K | black | 1.5 | 3.4 | - | 1500 | 14.4 | 22 |
| 4160406 | grey | 1.5 | 3.4 | 100 | - | 14.4 | 22 |
| 4160406K | grey | 1.5 | 3.4 | - | 1500 | 14.4 | 22 |
| 4160402 | blue | 1.5 | 3.4 | 100 | - | 14.4 | 22 |
| 4160402K | blue | 1.5 | 3.4 | - | 1500 | 14.4 | 22 |
| 4160414 | dark blue | 1.5 | 3.4 | 100 | - | 14.4 | 22 |
| 4160414K | dark blue | 1.5 | 3.4 | - | 1500 | 14.4 | 22 |
| 4160409 | orange | 1.5 | 3.4 | 100 | - | 14.4 | 22 |
| 4160409K | orange | 1.5 | 3.4 | - | 1500 | 14.4 | 22 |
| 4160407 | violet | 1.5 | 3.4 | 100 | - | 14.4 | 22 |
| 4160410 | yellow | 1.5 | 3.4 | 100 | - | 14.4 | 22 |
| 4160410K | yellow | 1.5 | 3.4 | - | 1500 | 14.4 | 22 |
| 4160405 | white | 1.5 | 3.4 | 100 | - | 14.4 | 22 |
| 4160405K | white | 1.5 | 3.4 | - | 1500 | 14.4 | 22 |
| 4160404 | red | 1.5 | 3.4 | 100 | - | 14.4 | 22 |
| 4160404K | red | 1.5 | 3.4 | - | 1500 | 14.4 | 22 |
| 4160408 | pink | 1.5 | 3.4 | 100 | - | 14.4 | 22 |
| 4160426 | blue/white | 1.5 | 3.4 | 100 | - | 14.4 | 22 |
| | | | | | | | |

Last Update (05.05.2021)
©2021 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.

LAPP

# MULTI-STANDARD SC 2.1

PRODUCT INFORMATION

| Article number | Core colour | Conductor cross-section (mm²) | Outer diameter [mm] | m/ring | m/box | Copper index (kg/km) | Weight (kg/km) |
|---|---|---|---|---|---|---|---|
| 4160426K | blue/white | 1.5 | 3.4 | - | 1500 | 14.4 | 22 |
| 4160444 | white/blue | 1.5 | 3.4 | 100 | - | 14.4 | 22 |
| 4160444K | white/blue | 1.5 | 3.4 | - | 1500 | 14.4 | 22 |
| 4160457 | white-yellow | 1.5 | 3.4 | - | 1500 | 14.4 | 22 |
| 4160500 | green/yellow | 2.5 | 4 | 100 | - | 24 | 37 |
| 4160500K | green/yellow | 2.5 | 4 | - | 900 | 24 | 37 |
| 4160511 | green | 2.5 | 4 | 100 | - | 24 | 37 |
| 4160503 | brown | 2.5 | 4 | 100 | - | 24 | 37 |
| 4160503K | brown | 2.5 | 4 | - | 900 | 24 | 37 |
| 4160501 | black | 2.5 | 4 | 100 | - | 24 | 37 |
| 4160501K | black | 2.5 | 4 | - | 900 | 24 | 37 |
| 4160506 | grey | 2.5 | 4 | 100 | - | 24 | 37 |
| 4160506K | grey | 2.5 | 4 | - | 900 | 24 | 37 |
| 4160502 | blue | 2.5 | 4 | 100 | - | 24 | 37 |
| 4160502K | blue | 2.5 | 4 | - | 900 | 24 | 37 |
| 4160514 | dark blue | 2.5 | 4 | 100 | - | 24 | 37 |
| 4160514K | dark blue | 2.5 | 4 | - | 900 | 24 | 37 |
| 4160509 | orange | 2.5 | 4 | 100 | - | 24 | 37 |
| 4160509K | orange | 2.5 | 4 | - | 900 | 24 | 37 |
| 4160507 | violet | 2.5 | 4 | 100 | - | 24 | 37 |
| 4160510 | yellow | 2.5 | 4 | 100 | - | 24 | 37 |
| 4160510K | yellow | 2.5 | 4 | - | 900 | 24 | 37 |
| 4160505 | white | 2.5 | 4 | 100 | - | 24 | 37 |
| 4160505K | white | 2.5 | 4 | - | 900 | 24 | 37 |
| 4160504 | red | 2.5 | 4 | 100 | - | 24 | 37 |
| 4160504K | red | 2.5 | 4 | - | 900 | 24 | 37 |
| 4160526 | blue/white | 2.5 | 4 | 100 | - | 24 | 37 |
| 4160544 | white/blue | 2.5 | 4 | 100 | - | 24 | 37 |
| 4160544K | white/blue | 2.5 | 4 | - | 900 | 24 | 37 |
| 4160600 | green/yellow | 4 | 4.6 | 100 | - | 38.4 | 49 |
| 4160600K | green/yellow | 4 | 4.6 | - | 600 | 38.4 | 49 |
| 4160611 | green | 4 | 4.6 | 100 | - | 38.4 | 49 |
| 4160603 | brown | 4 | 4.6 | 100 | - | 38.4 | 49 |
| 4160603K | brown | 4 | 4.6 | - | 600 | 38.4 | 49 |
| | | | | | | | |

Last Update (05.05.2021)
©2021 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16

LAPP

PRODUCT INFORMATION

# MULTI-STANDARD SC 2.1

| Article number | Core colour | Conductor cross-section (mm²) | Outer diameter [mm] | m/ring | m/box | Copper index (kg/km) | Weight (kg/km) |
|---|---|---|---|---|---|---|---|
| 4160601 | black | 4 | 4.6 | 100 | - | 38.4 | 49 |
| 4160601K | black | 4 | 4.6 | - | 600 | 38.4 | 49 |
| 4160606 | grey | 4 | 4.6 | 100 | - | 38.4 | 49 |
| 4160602 | blue | 4 | 4.6 | 100 | - | 38.4 | 49 |
| 4160602K | blue | 4 | 4.6 | - | 600 | 38.4 | 49 |
| 4160614 | dark blue | 4 | 4.6 | 100 | - | 38.4 | 49 |
| 4160614K | dark blue | 4 | 4.6 | - | 600 | 38.4 | 49 |
| 4160609 | orange | 4 | 4.6 | 100 | - | 38.4 | 49 |
| 4160609K | orange | 4 | 4.6 | - | 600 | 38.4 | 49 |
| 4160607 | violet | 4 | 4.6 | 100 | - | 38.4 | 49 |
| 4160610 | yellow | 4 | 4.6 | 100 | - | 38.4 | 49 |
| 4160610K | yellow | 4 | 4.6 | - | 600 | 38.4 | 49 |
| 4160605 | white | 4 | 4.6 | 100 | - | 38.4 | 49 |
| 4160604 | red | 4 | 4.6 | 100 | - | 38.4 | 49 |
| 4160604K | red | 4 | 4.6 | - | 600 | 38.4 | 49 |
| 4160626 | blue/white | 4 | 4.6 | 100 | - | 38.4 | 49 |
| 4160644 | white/blue | 4 | 4.6 | 100 | - | 38.4 | 49 |
| 4160700 | green/yellow | 6 | 5.1 | 100 | - | 57.6 | 67 |
| 4160700K | green/yellow | 6 | 5.1 | - | 400 | 57.6 | 67 |
| 4160711 | green | 6 | 5.1 | 100 | - | 57.6 | 67 |
| 4160703 | brown | 6 | 5.1 | 100 | - | 57.6 | 67 |
| 4160701 | black | 6 | 5.1 | 100 | - | 57.6 | 67 |
| 4160701K | black | 6 | 5.1 | - | 400 | 57.6 | 67 |
| 4160706 | grey | 6 | 5.1 | 100 | - | 57.6 | 67 |
| 4160706K | grey | 6 | 5.1 | - | 400 | 57.6 | 67 |
| 4160702 | blue | 6 | 5.1 | 100 | - | 57.6 | 67 |
| 4160702K | blue | 6 | 5.1 | - | 400 | 57.6 | 67 |
| 4160714 | dark blue | 6 | 5.1 | 100 | - | 57.6 | 67 |
| 4160714K | dark blue | 6 | 5.1 | - | 400 | 57.6 | 67 |
| 4160709 | orange | 6 | 5.1 | 100 | - | 57.6 | 67 |
| 4160709K | orange | 6 | 5.1 | - | 400 | 57.6 | 67 |
| 4160707 | violet | 6 | 5.1 | 100 | - | 57.6 | 67 |
| 4160710 | yellow | 6 | 5.1 | 100 | - | 57.6 | 67 |
| 4160705 | white | 6 | 5.1 | 100 | - | 57.6 | 67 |
| | | | | | | | |

Last Update (05.05.2021)
©2021 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16

LAPP

PRODUCT INFORMATION

# MULTI-STANDARD SC 2.1

| Article number | Core colour | Conductor cross-section (mm²) | Outer diameter [mm] | m/ring | m/box | Copper index (kg/km) | Weight (kg/km) |
|---|---|---|---|---|---|---|---|
| 4160704 | red | 6 | 5.1 | 100 | - | 57.6 | 67 |
| 4160704K | red | 6 | 5.1 | - | 400 | 57.6 | 67 |
| 4160726 | blue/white | 6 | 5.1 | 100 | - | 57.6 | 67 |
| 4160744 | white/blue | 6 | 5.1 | 100 | - | 57.6 | 67 |
| 4160800 | green/yellow | 10 | 6.8 | 100 | - | 96 | 120 |
| 4160811 | green | 10 | 6.8 | 100 | - | 96 | 120 |
| 4160803 | brown | 10 | 6.8 | 100 | - | 96 | 120 |
| 4160801 | black | 10 | 6.8 | 100 | - | 96 | 120 |
| 4160806 | grey | 10 | 6.8 | 100 | - | 96 | 120 |
| 4160802 | blue | 10 | 6.8 | 100 | - | 96 | 120 |
| 4160814 | dark blue | 10 | 6.8 | 100 | - | 96 | 120 |
| 4160809 | orange | 10 | 6.8 | 100 | - | 96 | 120 |
| 4160810 | yellow | 10 | 6.8 | 100 | - | 96 | 120 |
| 4160805 | white | 10 | 6.8 | 100 | - | 96 | 120 |
| 4160804 | red | 10 | 6.8 | 100 | - | 96 | 120 |
| 4160826 | blue/white | 10 | 6.8 | 100 | - | 96 | 120 |
| 4160844 | white/blue | 10 | 6.8 | 100 | - | 96 | 120 |
| 4160900 | green/yellow | 16 | 9 | 100 | - | 153.6 | 185 |
| 4160911 | green | 16 | 9 | 100 | - | 153.6 | 185 |
| 4160903 | brown | 16 | 9 | 100 | - | 153.6 | 185 |
| 4160901 | black | 16 | 9 | 100 | - | 153.6 | 185 |
| 4160906 | grey | 16 | 9 | 100 | - | 153.6 | 185 |
| 4160902 | blue | 16 | 9 | 100 | - | 153.6 | 185 |
| 4160914 | dark blue | 16 | 9 | 100 | - | 153.6 | 185 |
| 4160909 | orange | 16 | 9 | 100 | - | 153.6 | 185 |
| 4160910 | yellow | 16 | 9 | 100 | - | 153.6 | 185 |
| 4160905 | white | 16 | 9 | 100 | - | 153.6 | 185 |
| 4160904 | red | 16 | 9 | 100 | - | 153.6 | 185 |
| 4161000 | green/yellow | 25 | 10.2 | 100 | - | 240 | 260 |
| 4161011 | green | 25 | 10.2 | 100 | - | 240 | 260 |
| 4161003 | brown | 25 | 10.2 | 100 | - | 240 | 260 |
| 4161001 | black | 25 | 10.2 | 100 | - | 240 | 260 |
| 4161006 | grey | 25 | 10.2 | 100 | - | 240 | 260 |
| 4161002 | blue | 25 | 10.2 | 100 | - | 240 | 260 |
| | | | | | | | |

Last Update (05.05.2021)
©2021 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.

LAPP

# MULTI-STANDARD SC 2.1

PRODUCT INFORMATION

| Article number | Core colour | Conductor cross-section (mm²) | Outer diameter [mm] | m/ring | m/box | Copper index (kg/km) | Weight (kg/km) |
|---|---|---|---|---|---|---|---|
| 4161009 | orange | 25 | 10.2 | 100 | - | 240 | 260 |
| 4161010 | yellow | 25 | 10.2 | 100 | - | 240 | 260 |
| 4161005 | white | 25 | 10.2 | 100 | - | 240 | 260 |
| 4161004 | red | 25 | 10.2 | 100 | - | 240 | 260 |
| 4161100 | green/yellow | 35 | 11.7 | - | - | 336 | 360 |
| 4161111 | green | 35 | 11.7 | - | - | 336 | 360 |
| 4161101 | black | 35 | 11.7 | - | - | 336 | 360 |
| 4161106 | grey | 35 | 11.7 | - | - | 336 | 360 |
| 4161102 | blue | 35 | 11.7 | - | - | 336 | 360 |
| 4161105 | white | 35 | 11.7 | - | - | 336 | 360 |
| 4161104 | red | 35 | 11.7 | - | - | 336 | 360 |
| 4161200 | green/yellow | 50 | 13.9 | - | - | 480 | 535 |
| 4161211 | green | 50 | 13.9 | - | - | 480 | 535 |
| 4161201 | black | 50 | 13.9 | - | - | 480 | 535 |
| 4161202 | blue | 50 | 13.9 | - | - | 480 | 535 |
| 4161300 | green/yellow | 70 | 16 | - | - | 672 | 735 |
| 4161301 | black | 70 | 16 | - | - | 672 | 735 |
| 4161400 | green/yellow | 95 | 18.2 | - | - | 912 | 930 |
| 4161401 | black | 95 | 18.2 | - | - | 912 | 930 |
| 4161402 | blue | 95 | 18.2 | - | - | 912 | 930 |
| 4161500 | green/yellow | 120 | 19.8 | - | - | 1152 | 1160 |
| 4161501 | black | 120 | 19.8 | - | - | 1152 | 1160 |
| 4161502 | blue | 120 | 19.8 | - | - | 1152 | 1160 |

Last Update (05.05.2021)
©2021 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16