

Short Circuit Ratings

Product: 100-K05DJ10

Description: 100-K MCS Mini Contactors, Screw Type Terminals, 5 A, System Control Voltage: 24 (17...30)V DC Diode, 3 N.O. Main Contacts, 1 N.O. Auxiliary Contact, Single Pack: Quantity of 1

Operational Rating	Dual Element Time Delay Fuses			Circuit Breakers							Rating Reference	File Ref: UL	File Ref: CSA	Comments
	SCCR [kA]	Max Fuse Size [A]	Fuse Class	CB Type	UL CMC Type	Catalog Numbers	SCCR [kA]	SCCR [kA]	SCCR [kA]	SCCR [kA]				
							480V	480Y/277V	600V	600Y/347V				
5A (AC3/4)	50	30	CC, J	UL 508 Manual Motor Controller	--	140M-C2E-A16 to 140M-C2E-B16	65	--	47	--	Instruction Sheet	E41850	cULus	
5A (AC3/4)	50	30	CC, J	UL 508 Manual Motor Controller	--	140M-C2E-B25 to 140M-C2E-B63	65	--	30	--	Instruction Sheet	E41850	cULus	
5A (AC3/4)	5	40	K5, RK5	UL 508 Type E Comb. Motor Controller	F (2 Comp)	140M-C2E-A16 to 140M-C2E-B16	--	65	--	47	Instruction Sheet	E41850	cULus	
5A (AC3/4)	5	40	K5, RK5	UL 508 Type E Comb. Motor Controller	F (2 Comp)	140M-C2E-B25 to 140M-C2E-B40	--	65	--	30	Instruction Sheet	E41850	cULus	
5A (AC3/4)	5	40	K5, RK5	UL 508 Type E Comb. Motor Controller	F (2 Comp)	140M-C2E-B63	--	65	--	--	Instruction Sheet	E41850	cULus	
5A (AC3/4)	--	--	--	UL 489 MCCB	--	--	--	--	--	--	Instruction Sheet	E41850	cULus	
5A (AC3/4)	--	--	--	UL 489 MCP	--	--	--	--	--	--	Instruction Sheet	E41850	cULus	