

Catalog Number: HSB187-2
Product ID: 7TCA017300R0327
UPC Number: 78621050556
EAN Number: 05414363104155
Status: Active



Thin Wall Heat Shrink Tubing in Dispenser Box - 3/16 Inch Expanded Inside Diameter - 9.5 Meters Red

Actual

North American Specifications (UNSPSC)

UNSPSC	39121723 Heat shrinkable tube
IGCC	5073 Heat shrinkable tube
Brand Name	Shrink-Kon
Type	Thin-Wall Heat-Shrinkable Tubing
Shrink Ratio	2:1
Thickness	Thin
Length	31.17 in ; 9.5 m
Dielectric Strength	280 V/Mil (11kV/mm)
Continuous Operating Temperature	-67 Degrees F (-55C) to 212 Degrees F (100 C)
Minimum Shrink Temperature	230 Degrees F (110 C)
Flammability	Self Extinguishing within 1.97 Seconds
Water Absorption	0.03%
Color	Red

European Specifications (ETIM)

ETIM	EC000217 Shrink tubing
Type	Heat-shrink
Model	Thin-walled
Shrink rate	2:1
Inner diameter before heat-shrink	4.8mm
Inner diameter after heat-shrink	2.4mm
Nominal diameter inch	3/16 inch
Wall thickness after shrinking	0.5mm
Length	9.5m
Operation temperature	-55-+135°C
Colour	Red
Material	Polyolefin (PO-X)
Halogen free	N
With inner glue	N
Printable	N
UL approval	N

Packaging

Inner Quantity	1
Inner Dimensions (inches)	6.7x2.4x6.7
Outer Quantity	60
Outer Dimensions (inches)	20.9x15.8x22.5
Weight Uom	35.8 lbs. per 100

Documents / Support Tools

Technical Drawing / Data Sheet	WSD-001466
--------------------------------	------------

For further technical assistance, please contact us...

ABB Installation Products - USA
 860 Ridge Lake Blvd.
 Memphis, TN 38120
www.tnb.com

ABB Installation Products Technical Support
 MS 3B-50
 860 Ridge Lake Blvd.
 Memphis, TN 38120

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com