





标 记
MARKECN编号/变更内容
ECN NO/DEFINITION修 改
REVISE日 期
DATE核 准
APPROVE

Materials and Electroplating

- ①. Screw: M2.5, iron, galvanized, straight groove
②. Plastic body: PA66
③. Clip: Copper, nickel plated
④. Square box: iron, nickel plated
⑤. Plastic cover plate: PA66
Electrical performance
Rated voltage: 300V
Rated current: 15A
Contact resistance: 20m Ω (Max)
Insulation resistance: 500M Ω/DC500V
Voltage endurance: AC1500V/1Min
Wire diameter used: 28-12AWG
mechanical properties
Temperature range: -40 °C~+105 °C
Instantaneous temperature: +250 °C for 5 seconds
Torque: 0.4Nm (3.6 Ib. in)
Stripping length: 7-8mm



2	方盒	铁	镀镍	
1	底座	PA66	绿色	
序号	品名	材质	电镀/颜色	备注

	深圳市虹成电子有限公司		品 名	接线端子																			
			TITLE																				
			料 号	HC-JXDZK-5.08-6P-A																			
			PART NO																				
GENERAL TOLERANCES (UNLESS SPECIFIED)			比 列	1 : 1																			
			单 位	MM	制 图																		
			UNIT		DRAW																		
<table border="1" data-bbox="1413 1359 1523 1414"><tr><th colspan="3">公差参数</th></tr><tr><th>尺寸</th><th>DimP</th><th>DimL</th></tr><tr><td>2-6P</td><td>±0.10</td><td>±0.20</td></tr><tr><td>7-12P</td><td>±0.20</td><td>±0.30</td></tr><tr><td>13-18P</td><td>±0.25</td><td>±0.40</td></tr><tr><td>19-24P</td><td>±0.30</td><td>±0.50</td></tr></table>			公差参数			尺寸	DimP	DimL	2-6P	±0.10	±0.20	7-12P	±0.20	±0.30	13-18P	±0.25	±0.40	19-24P	±0.30	±0.50	X. xxx ± 0.15	张 数	审 核
			公差参数																				
尺寸	DimP	DimL																					
2-6P	±0.10	±0.20																					
7-12P	±0.20	±0.30																					
13-18P	±0.25	±0.40																					
19-24P	±0.30	±0.50																					
			± 0.25	1 OF 1	夏操云																		
			± 0.35	PART NO	CHECKED																		
			版 本	批 准																			
			REV	APPROVE																			
			A	赵亮亮																			