

OT FIT 40/220...240/1A0 CS

OPTOTRONIC FIT CS | Compact Constant Current LED Drivers – Non dimmable



Areas of application

- Suitable for downlights, spotlights and LED panels
- Suitable for luminaires of protection classes I and II

Product family benefits

- High quality of light thanks to low output ripple current
- High flexibility due to four different output currents
- Small housing for flexible luminaire designs
- High efficiency

Product family features

- Supply voltage: 220...240 V
- Line frequency: 50 Hz | 60 Hz
- Line voltage: 198...264 V
- Safety according to EN 61347-1, 61347-2-13, 62384
- RI suppression: to EN 55015
- Line harmonics according to EN 61000-3-2
- Immunity according to EN 61547
- Lifetime: up to 50,000 h (temperature at $T_c = 70^\circ\text{C}$, max. 10 % failure rate)
- Cable clamp kit for independent mounting

Technical data

Electrical data

Nominal input voltage	220...240 V
Mains frequency	50...60 Hz
Input voltage AC	198...264 V
Total harmonic distortion	< 10 % ¹⁾
Power factor λ	0.98
ECG efficiency	90 % ²⁾
Device power loss	4.9 W ³⁾
Protective conductor current	<0.7 mA
Inrush current	< 16 A ⁴⁾
Max. ECG no. on circuit breaker 10 A (B)	16
Max. ECG no. on circuit breaker 16 A (B)	25
Max. ECG no. on circuit breaker 25 A (B)	-
Surge capability (L/N-Ground)	2 kV
Surge capability (L-N)	1 kV
Nominal output voltage	25...42 V
U-OUT (working voltage)	60 V
Nominal output current	800 / 900 / 1050 / 950 mA
Output current tolerance	± 7.5 %
Output ripple current (100 Hz)	< 5 %
Nominal output power	20...44 W
Galvanic isolation	SELV


1) At full load, 230 V, 50 Hz / see graphs

2) At full load and 230 V / At 50 Hz

3) At 230 V, Input power 49 W max.

4) $t_{width} = 100 \mu s$ (measured at 50 % I_{peak})

Dimensions & weight



Product datasheet

Mounting hole spacing, length	88.0 mm
Mounting hole spacing, width	34.0 mm
Product weight	110.00 g
Cable cross-section, input side	0.5...1.5 mm ²
Cable cross-section, output side	0.5...1.5 mm ²
Wire preparation length, input side	7...8 mm
Wire preparation length, output side	7...8 mm

Colors & materials

Casing material	Plastic
-----------------	---------

Temperatures & operating conditions

Ambient temperature range	-20...+50 °C
Maximum temperature at tc test point	75 °C
Max.housing temperature in case of fault	110 °C
Permitted rel. humidity during operation	5...85 %

Lifespan

ECG lifetime	50000 / 30000 h ¹⁾
--------------	-------------------------------

¹⁾ T_c = 70°C, with max. 10% failure rate / T_c = 80°C, with max. 10% failure rate

Additional product data

Encapsulated	No
--------------	----

Capabilities

Dimmable	No
Overheating protection	Automatic reversible
Overload protection	Automatic reversible
Short-circuit protection	Automatic reversible
No-load proof	Yes
Max. cable length to lamp/LED module	2.0 m
Suitable for fixtures with prot. class	II
Type of connection, output side	Push terminal

Certificates & standards

Approval marks – approval	CCC / CE / RCM / ENEC 05
Standards	Acc. to IEC 61347-1/Acc. to IEC 61347-2-13/Acc. to IEC 62384/Acc. to CISPR 15/Acc. to IEC 61000-3-2/Acc. to IEC 61000-3-3/Acc. to IEC 61547
Type of protection	IP20

Product datasheet

Logistical data

Temperature range at storage	-20...80 °C
Commodity code	850440829000

Download Data

File	
	User instruction OPTOTRONIC LED Power Supply
	Product Datasheet 730301_OT FIT 40220-2401A0 CS
	Certificates Certificate 2196588.02 ENEC
	Certificates CCC Certificate 2018171002002233
	Certificates CCC Certificate 2018171002002234
	Declarations of conformity 489246_DoC_OT FIT CS
	Declarations of conformity EU Declaration of Conformity 3667905

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899435650	OT FIT 40/220...240/1A0 CS	Shipping carton box 20	228 mm x 208 mm x 78 mm	3.70 dm ³	2306.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.