



SPECIFICATIONS:

Current Rating: 3A AC,DC
Voltage Rating: 250V AC,DC
Temperature Range: -40°C ~ +105°C
Contact Resistance: 20mΩ Max
Insulation Resistance: 1000MΩ Min
Withstanding Voltage: 1000V AC/minute
Material: Nylon 66,UL94V-0(White)

Ordering Information & Dimensions

Circuits	Dimensions(mm)		Circuits	Dimensions(mm)	
	A	B		A	B
2P	2.50	5.70	12P	27.50	30.70
3P	5.00	8.20	13P	30.00	33.20
4P	7.50	10.70	14P	32.50	35.70
5P	10.00	13.20	15P	35.00	38.20
6P	12.50	15.70	16P	37.50	40.70
7P	15.00	18.20	17P	40.00	43.20
8P	17.50	20.70	18P	42.50	45.70
9P	20.00	23.20	19P	45.00	48.20
10P	22.50	25.70	20P	47.50	50.70
11P	25.00	28.20			

CJTconn

CHANGJIANG CONNECTORS CO.,LTD.

Unit	Scale	Sheet
mm	4:1	1 of 1
Draw By:		Approved :
Dlankul Wan		Jack Yln

Title :
2.50mm Pitch

Housing

A2	CHANGE THE DRAW NO.	2019.06.17
A1	CHANGE THE SIZE	2017.02.14
A0	NEW RELEASE	2012.11.16
REV	DESCRIPTION	DATE

General Tolerance	
x.xx±0.25	PROJECT
x.xx±0.20	
x.xxx±0.15	

DRAW NO : C2504AH-XP-WH
REV A2