

You are here: [Products](#) » [Heatsinks f.cool](#) » [Profile heatsinks and fluid coolers](#) » [Extruded heatsinks for PCB mounting](#) » [SK 104 ... STCSK 104 ... STICK 104 ... STCB](#) » **SK 104 38,1**



▼ Heatsinks f.cool

- ▼ Profile heatsinks and fluid coolers
 - Standard extruded heatsinks
 - Extruded heatsinks for lock-in retaining spring
 - **Extruded heatsinks for PCB mounting**
 - Extruded heatsinks for DC/DC converter
 - Retaining springs for transistors
 - U-Extruded heatsinks
 - Die-cast heatsinks
 - Fin coolers
 - Fluid coolers
 - Aluminium flat-, quadrangular-, angled-, U- and T-profiles
- Heatsinks and active heatsinks for processors
- Board Level heatsinks
- Cooling aggregates
- Accessories for electronic components

► Cases f.case

► Connectors f.con

Extruded heatsinks for PCB mounting

SK 104 ... STC
SK 104 ... STIC
SK 104 ... STCB

SK 104 38,1 STC

34.9 x 12.7 mm, for semiconductor clip-mounting

Data sheet

add to request



Features Technical Drawing Variants Service Accessories / related products

way of fixation	transistor clip mounting
width	34.9 mm
height	12.7 mm
plate thickness	1.5 mm
length	38.1 mm
thermal resistance R_{th}	11 K/W
drilling pattern	TO 220
mounting method	with solder pin
surface	black anodised