

IP68 防水接线器/ waterproof connector

KH-M685-TL-4P



单孔/Single
2P



单孔/Single
3P



单孔/Single
4P



单孔/Single
5P



双孔/Double
3P



NSW

UK
CA

CB

RoHS

产品参数/Technical data

型号 Model	KH-M685-TL-4P		
材料 Material	UL94V-2 Fire and flame retardant		
额定输出 Rated power	IEC/NSW:32A 450VAC ETL:18A 300VAC		
防护等级 IP code	IP68		
接线端子 Terminal	2P/3P/4P/5P		
工作温度 Working	T105		
接线范围 Rated connecting capacity	欧规 European:0.5 ~ 4.0mm² 澳规 Australia:0.5 ~ 4.0mm² 美规 American:SJOW 12-14AWG		
密封胶塞/seal plug			
胶塞孔径/plug aperturer	8mm	12mm	14mm
适用线径/Available cable diameter (橡胶圆线/Round rubber cable)	3*M25(4-8mm)	3*M25(8-12mm)	3*M25(10-14mm)
防水测试 Testing	20M 150hours		
参考剥线长度 Refer to stripping length	外剥线 External stripping 25mm 内剥线 Internal stripping 7mm		
产品尺寸 Product Size(参考实际尺寸图)	94.38*97.1mm (Refer to actual drawing)		
认证 Certification	ENEC,CE,UKCA,ETL,NSW,CB,ROHS		
产品应用/Application	水底/Underwater(淡水 fresh water) 地埋/Underground		
注/Mark: 1.不能使用在盐碱土壤/Do not use in saline soil 2.不能长期接触油性物质或浸泡在油污中/Do not contact oily substances or soak in oil for a longtime 3.不建议长期在日照暴晒下使用/Longtime exposed under sunshine is not recommended			

接线步骤/Wiring steps

01



扭开螺帽套筒，取出接线内芯
Twist off the nut sleeve and remove the wiring core

02



将线材穿过螺帽套筒
Thread the cable through the nut

03



线材插入接线内芯后螺丝固定
The wire is inserted into the inner core of the connection and fixed by a screw

04



拧紧两端螺帽主体，接线完成
Twist and tighten the cable glands