

A



PART NO.:

①Series Name:X10C25=1.00mm Pitch(H:2.50mm)

②Number of terminals:XX=02-35PIN

③Plating : G:Gold Flash Over Nickel

T: Tin Over Nickel

④Z:positive needle F:negative needle

3.PERFORMANCE:

3.1: CURRENT RATING:0.5A/PIN

3.1: CURRENT RATING:0.5A/PIN
3.2: VOLTAGE RATING:50V(AC/DC)
3.3: CONTACT RESISTANCE: INITIAL VALUE 30mOHM Max.

3.4:INSULATION RESISTANCE:500MOHM Min.

3.5:DIELECTRIC WITHSTANDING VOLTAGE:250V AC FOR 1MINUTE

3.6:DURABILT: 20 TIMES Min

3.7: OPERATING TEMPERATURE: $-40^{\circ}\text{C} \sim +85^{\circ}\text{C}$
OPERATING HUMIDITY RANGE: 30% TO 95%

C

DESIGN
CHECKED
APPROVED

VIEW: 

MODEL TYPE:	FPC CONNECTOR
-------------	---------------

PART NO.:

Part No.:	X10C2526GZ
-----------	------------

DWG. NO. :	XTC25269Z
------------	-----------

DWG NO.:

		X10C2526GZ

SCALE	PAGE
-------	------

N/A	1/1
-----	-----

4

4

www.helloxkb.com	www.helloxkb.cn	www.xk-dq.cn
------------------	-----------------	--------------

XKB INDUSTRIAL PRECISION CO.,LIMITED

1

2

2

4