

Amphenol CABLES ON DEMAND

75+ Years of Interconnect Manufacturing Experience



1-866-223-2860
Live Support
Email Us
 Chat with me

Search Home About Contact Us Help Your Account Shopping Cart - 0 items

Shop By Category

- Adapters
- Audio Video Monitor Cables
- CAT-5e • CAT-6 • Telco Cables
- Coaxial Cables
- Connectors & Cages
- CX4 Cables • InfiniBand Cables
- DisplayPort Cables & Adapters
- D-Sub Cables • D-Sub Adapters
- Factory Automation Cables
- Fiber Optic Patch Cables
- Fibre Channel & DIN Cables
- GPIB Cables (IEEE-488 Cables)
- HDMI Cables (High Speed HDMI)
- Power Cords
- QSFP Cables • QSFP+ Cables
- QSFP+ Modules & Loopbacks
- SAS Cables • SATA Cables
- SCSI Cables • VHDCI Cables
- SFP Cables • SFP Modules
- SFP+ Cables • SFP+ Modules
- Test Cards • Evaluation Boards
- USB Cables

Shop By Application

- 20 Percent OFF High Speed Sale
- 30 Percent OFF CAT5e/6/6a Sale
- 25 Percent OFF Coupon Code
- Custom Cables & Cable Kits
- Data Center Cable Solutions
- Home Theater AV Cable Center
- Active Optical Cable Solutions

More ways to Shop

- Hot Items
- New Items

D-Sub Cables • D-Sub Adapters » D-Subminiature (D-Sub) Cables » 50-Pin D-Sub Cable (DB50) » CS-DSDMDB50MM

50-Pin (DB50) Deluxe D-Sub Cable - Copper Shielded - Male / Male



[Click for larger image](#)

50-pin (DB50) Copper Shielded High Density Male/Male D-Sub Cables by Amphenol provide exceptional performance in commercial, industrial or enterprise applications where longevity and repeated disconnects are required. Our fully assembled Deluxe HD D-Sub Cable integrates copper tape + aluminum mylar shielded 26 AWG data-grade wire with pre-terminated DB50 male d-sub connectors. Perfect for RS232 serial data, prototype, control and low-voltage applications using the 50-pin DB50 interface.

Similar Products

[50-Pin \(DB50\) Deluxe D-Sub Cable - Copper Shielded - Male / Female](#)



Product Features:

- Get \$75 OFF All D-Sub Cable Orders Over \$300 Thru 2/28
- 50-Pin (DB50) Deluxe Fully Populated D-Sub Cable Assembly by Amphenol
- Connectors: DB50 male to DB50 male D-Sub connectors pre-installed
- Cable: 26 AWG UL listed with copper tape + aluminum mylar shields
- Straight-through wiring (i.e. pin 1 to pin 1) design per industry standards
- Perfect for low-voltage signals & DCE/DTE RS232 serial communications
- 100% EMI/RFI shielded design combines aluminum mylar and copper tape
- Fully populated with Gold-plated contacts for superior signal continuity
- Rugged UL94V-0 flame-resistant PVC jacket and overmold for strain relief
- 300V voltage handling capacity at temperatures up to 80 degrees Celsius
- Available in multiple cable lengths to meet your specific requirements
- Cables can be easily cut in half and custom terminated for prototyping
- RoHS compliant

Item#	Color	Length	Qty 1-50	Qty >50	Availability	Order Qty
CS-DSDMDB50MM-002.5	Gray	2.5ft		In Stock		<input type="text"/>
CS-DSDMDB50MM-005	Gray	5ft		In Stock		<input type="text"/>
CS-DSDMDB50MM-010	Gray	10ft		In Stock		<input type="text"/>
CS-DSDMDB50MM-015	Gray	15ft		In Stock		<input type="text"/>
CS-DSDMDB50MM-025	Gray	25ft		In Stock		<input type="text"/>

Add all entered quantities to cart ->

[Same Day Shipping](#)



Sign up for our E-mail Newsletter

Privacy by SafeSubscribeSM