



Ordering Information:
C4201WRSB-XP - *** - ***
1 2 3

- 1.Part NO.
- 2.Color:
(Blank): Black
IV: Ivory
- 3.Finish:
(Blank): Tin over Nickel
G: Gold over Nickel(Au:1µin[0.03µm] Min)
G3: Gold over Nickel(Au:3µin[0.08µm] Min)
G10: Gold over Nickel(Au:10µin[0.25µm] Min)
G15: Gold over Nickel(Au:15µin[0.38µm] Min)
G30: Gold over Nickel(Au:30µin[0.76µm] Min)

SPECIFICATIONS:

Current Rating: 9A AC,DC
Voltage Rating: 600V AC,DC
Temperature Range: -55°C ~ +105°C
Contact Resistance: 10mΩ Max
After environmental testing: 20mΩ Max
Insulation Resistance: 1000MΩ Min
Withstanding Voltage: 1500V AC/minute
Pin Material:Brass
Material: LCP,UL94V-0

Ordering Information & Dimensions

Part NO.	Dimensions(mm)	
	A	B
C4201WRSB-2P	4.19	9.72
C4201WRSB-3P	8.38	13.91
C4201WRSB-4P	12.57	18.10
C4201WRSB-5P	16.76	22.29
C4201WRSB-6P	20.95	26.48
C4201WRSB-7P	25.14	30.67
C4201WRSB-8P	29.33	34.86
C4201WRSB-9P	33.52	39.05
C4201WRSB-10P	37.71	43.24
C4201WRSB-11P	41.90	47.43
C4201WRSB-12P	46.09	51.62
C4201WRSB-13P	50.28	55.81
C4201WRSB-14P	54.47	60.00
C4201WRSB-15P	58.66	64.19

CJTconn CHANGJIANG CONNECTORS CO.,LTD.

Unit	Scale	Sheet	TITLE
mm	2:1	1 of 1	
DRWN	CHK'D	APPR	4.19mm PITCH 90° SINGLE ROW DIP WAFER
Dengchun Yi	Diankui Wan	Jack Yin	
General Tolerances		THIRD ANGLE PROJECTION	DRAWING NO. C4201WRSB-XP
x.x±0.25 x.xx±0.20 x.xxx±0.15 ANGLES ±1°			

REV	DESCRIPTION	DATE
A3	CHANGE THE SIZE	2020.11.05
A2	CHANGE THE DRAWING	2020.09.08
A1	CHANGE THE DRAWING	2019.11.30
A0	NEW RELEASE	2015.03.11

REV
A3