



钜地半导体  
Tudi Semiconductor

## Product Specification

AT24C1024BN-SH25-T-TUDI

I<sup>2</sup>C-Compatible(2-wire)Serial EEPROM  
1-Mbit(131072\*8)

网址 [www.sztdbdt.com](http://www.sztdbdt.com) 🔍

**用芯智造 · 卓越品质**

**semiconductor device  
manufacturer**

- Design
- research and development
- production
- and sales




## Features

- Low voltage and standard voltage operation available
  - 1.7V ( $V_{CC} = 1.7V - 5.5$ )
  - 2.5V ( $V_{CC} = 2.5V - 5.5$ )
- Internally organized 131,072 x 8
- 2-wire serial interface
- Schmitt Triggers, filtered inputs for noise suppression
- Bidirectional data transfer protocol
- 400kHz (1.7V) and 1MHz (2.5V) compatibility
- Write Protect pin for hardware data protection
- 256-byte Page Write mode
  - Partial page writes allowed
- Random and Sequential Read modes
- (5ms max)
- High reliability
  - Endurance: 1,000,000 write cycles
  - Data retention: 40 years
- Green package options (Pb/Halide-free/RoHS Compliant)
  - 8-lead JEDEC SOIC, 8-lead EIAJ SOIC, 8-lead TSSOP, and 8-ball WLCSP
- Die sale options: wafer form and tape and reel available

## Description

The AT24C1024 provides 1,048,576 bits of Serial Electrically Erasable and Programmable Read-Only Memory (EEPROM) organized as 131,072 words of eight bits each. The device's cascadable feature allows up to four devices to share a common 2-wire bus. The device is optimized for use in many industrial and commercial applications where low power and low voltage operation are essential. The devices are available in space-saving 8-lead JEDEC SOIC, 8-lead EIAJ SOIC, 8-lead TSSOP, and 8-ball DIP. In addition, the entire family is available in 1.7V and 2.5V (2.5V) versions.





## Block Diagram




Figure 1





| Position | A   | B   | C   |
|----------|-----|-----|-----|
| 1        | VCC | –   | SDA |
| 2        | –   | SCL | –   |
| 3        | WP  | –   | A2  |
| 4        | –   | A1  | –   |
| 5        | NC  | –   | GND |

Table 2

DEVICE/PAGE ADDRESSES (A2 and A1): The A2 and A1 pins are device address inputs that are hard wire for the AT24C1024. Four 1M devices may be addressed on a single bus system (device addressing is discussed in detail under the Device Addressing section).

SERIAL DATA (SDA): The SDA pin is bi-directional for serial data transfer. This pin is open-drain driven and may be wire-ORed with any number of other open-drain or open- collector devices.

SERIAL CLOCK (SCL): The SCL input is used to positive edge clock data into each EEPROM device and negative edge clock data out of each device.

WRITE PROTECT (WP): The 24C1024has a Write Protect pin that provides hardware data protection. The Write Protect pin allows normal read/write operations when connected to ground (GND). When the Write Protection pin is connected to Vcc, the write protection feature is enabled and operates as shown in the following **Table 2**.

| WP Pin Status | AT24C1024                    |
|---------------|------------------------------|
| At VCC        | Full(1024K)Array             |
| At GND        | Normal Read/Write Operations |

Table 3

## Functional Description

### 1. Memory Organization

AT24C1024, 1M SERIAL EEPROM: Internally organized with 512 pages of 256 bytes each, the 1M requires a 17-bit data word address for random word addressing.

### 2. Device Operation

CLOCK and DATA TRANSITIONS: The SDA pin is normally pulled high with an external device. Data on the SDA pin may change only during SCL low time periods (see **Figure 2**). Data changes during SCL high periods will indicate a start or stop condition as defined below.

START CONDITION: A high-to-low transition of SDA with SCL high is a start condition which must precede any other command (see **Figure 3**).

STOP CONDITION: A low-to-high transition of SDA with SCL high is a stop condition. After a read sequence, the stop command will place the EEPROM in a standby power mode (see **Figure 3**).

ACKNOWLEDGE: All addresses and data words are serially transmitted to and from the EEPROM in 8-bit words. The EEPROM sends a "0" to acknowledge that it has received each word. This happens during the ninth clock cycle.

STANDBY MODE: The AT24C1024features a low-power standby mode which is enabled: (a) upon power-up and (b) after the receipt of the STOP bit and the completion of any internal operations.

MEMORY RESET: After an interruption in protocol, power loss or system reset, any two-wire part can be reset by following these steps:

1. Clock up to 9 cycles.
2. Lock SDA high in each cycle while SCL is high.
3. Create a start condition and a stop condition.






Figure 2. Data Validity




Figure 3. Start and Stop Definition




Figure 4. Output Acknowledge



### 3. Device Addressing

The 1M EEPROM devices all require an 8-bit device address word following a start condition to enable the chip for a read or write operation (see **Figure 5**)

The device address word consists of a mandatory "1", "0" sequence for the first four most significant bits as shown. This is common to all the Serial EEPROM devices.

The 1M EEPROM uses A2 and A1 device address bits and one word address bit to allow as much as four devices on the same bus. These 2 device address bits must be compared to their corresponding hardwired input pins. The A2 and A1 pins use an internal proprietary circuit that biases them to a logic low condition if the pins are allowed to float.

The eighth bit of the device address is the read/write operation select bit. A read operation is initiated if this bit is high and a write operation is initiated if this bit is low.

Upon a compare of the device address, the EEPROM will output a "0". If a compare is not made, the chip will return to a standby state.

| MSB |     |     |     | LSB |     |     |     |
|-----|-----|-----|-----|-----|-----|-----|-----|
| 1   | 0   | 1   | 0   | A2  | A1  | B16 | R/W |
| B15 | B14 | B13 | B12 | B11 | B10 | B9  | B8  |
| B7  | B6  | B5  | B4  | B3  | B2  | B1  | B0  |


**Figure 5. Device Address and two 8-bit data word address**

**DATA SECURITY:** The AT24C1024 has a hardware data protection scheme that allows the user to write protect the entire memory when the WP pin is at VCC.




#### 4. Write Operations

**BYTE WRITE:** A write operation requires two 8-bit data word address following the device address word and acknowledgment. Upon receipt of this address, the EEPROM will again respond with a "0" and then clock in the first 8-bit data word. Following receipt of the 8-bit data word, the EEPROM will output a "0" and the addressing device, such as a microcontroller, must terminate the write sequence with a stop condition. At this time the EEPROM enters an internally timed write cycle,  $t_{WR}$ , to the nonvolatile memory. All inputs are disabled during this write cycle and the EEPROM will not respond until the write is complete (see **Figure 6**).



**Figure 6. Byte Write**

**PAGE WRITE:** The Page Write mode allows up to 256 bytes to be written in a single Write cycle. A page write is initiated the same as a byte write, but the microcontroller does not send a stop condition after the first data word is clocked in. Instead, after the EEPROM acknowledges receipt of the first data word, the microcontroller can transmit up to 255 more data words. The EEPROM will respond with a "0" after each data word received. The microcontroller must terminate the page write sequence with a stop condition (see **Figure 7**).



**Figure 7. Page Write**

The data word address lower eight bits are internally incremented following the receipt of each data word. The higher data word address bits are not incremented, retaining the memory page row location. When the word address, internally generated, reaches the page boundary, the following byte is placed at the beginning of the same page. If more than 256 data words are transmitted to the EEPROM, the data word address will "roll over" and previous data will be overwritten.

**WRITE IDENTIFICATION PAGE:** The Identification Page (256 bytes) is an additional page which can be written and (later) permanently locked in Read-only mode. It is written by issuing the Write Identification Page instruction. This instruction uses the same protocol and format as Page Write (into memory array), except for the following differences:

- Device type identifier = 1011b
- MSB address bits B16/B8 are don't care except for address bit B10 which must be "0".  
LSB address bits B7/B0 define the byte address inside the Identification page.





If the Identification page is locked, the data bytes transferred during the Write Identification Page instruction are not acknowledged (NoAck).

ACKNOWLEDGE POLLING: Once the internally timed write cycle has started and the EEPROM inputs are disabled, acknowledge polling can be initiated. This involves sending a start condition followed by the device address word. The read/write bit is representative of the operation desired. Only if the internal write cycle has completed will the EEPROM respond with a "0", allowing the read or write sequence to continue.



## 5. Read Operations

Read operations are initiated the same way as write operations with the exception that the read/write select bit in the device address word is set to "1". There are three read operations: current address read, random address read and sequential read.

### CURRENT ADDRESS READ:

The internal data word address counter maintains the last address accessed during the last read or write operation, incremented by one. This address stays valid between operations as long as the chip power is maintained. The address "roll over" during read is from the last byte of the last memory page to the first byte of the first page. The address "roll over" during write is from the last byte of the current page to the first byte of the same page. Once the device address with the read/write select bit set to "1" is clocked in and acknowledged by the EEPROM, the current address data word is serially clocked out. The microcontroller does not respond with an input "0" but does generate a following stop condition (see **Figure 8**).




Figure 8. Current Address Read

### RANDOM READ:

A random read requires a "dummy" byte write sequence to load in the data word address. Once the device address word and data word address are clocked in and acknowledged by the EEPROM, the microcontroller must generate another start condition. The microcontroller now initiates a current address read by sending a device address with the read/write select bit high. The EEPROM acknowledges the device address and serially clocks out the data word. The microcontroller does not respond with a "0" but does generate a following stop condition (see **Figure 9**).





Figure 9. Random Read



**SEQUENTIAL READ:** Sequential reads are initiated by either a current address read or a random address read. After the microcontroller receives a data word, it responds with an acknowledge. As long as the EEPROM receives an acknowledge, it will continue to increment the data word address and serially clock out sequential data words. When the memory address limit is reached, the data word address will "roll over" and the sequential read will continue. The sequential read operation is terminated when the microcontroller does not respond with a "0" but does generate a following stop condition (see **Figure 10**).



**Figure 10. Sequential Read**

**READ IDENTIFICATION PAGE:** The Identification Page (256 bytes) is an additional page which can be written and (later) permanently locked in Read-only mode.

The Identification Page can be read by issuing an Read Identification Page instruction. This instruction uses the same protocol and format as the Random Address Read (from memory array) with device type identifier defined as 1011b. The MSB address bits B16/B8 are don't care, the LSB address bits B7/B0 define the byte address inside the Identification Page. The number of bytes to read in the ID page must not exceed the page boundary (e.g.: when reading the Identification Page from location 10d, the number of bytes should be less than or equal to 246, as the ID page boundary is 256 bytes)

**LOCK IDENTIFICATION PAGE:** The Lock Identification Page instruction (Lock ID) permanently locks the Identification page in Read-only mode. The Lock ID instruction is similar to Byte Write (into memory array) with the following specific conditions:

Device type identifier = 1011b

Address bit B10 must be '1'; all other address bits are don't care

The data byte must be equal to the binary value xxxx xx1x, where x is don't care





## Electrical Characteristics

Absolute Maximum Stress Ratings:

- DC Supply Voltage ..... -0.3V to +6.5V
- Input / Output Voltage ..... GND-0.3V to VCC+0.3V
- Storage Temperature ..... -65°C to +150°C
- Electrostatic pulse (Human Body model) ..... 8000V

Comments:

Stresses above those listed under "Absolute Maximum Ratings" may cause permanent damage to this device. These are stress ratings only. Functional operation of this device at these or any other conditions above those indicated in the operational sections of this specification is not implied or intended. Exposure to the absolute maximum rating conditions for extended periods may affect device reliability.

## DC Electrical Characteristics

Applicable over recommended operating range from (unless otherwise noted):

| AT24C1024                 | TA = -40°C to +85°C  | VCC = +1.7V to +5.5V<br>CL=100 pF |      |         |      |                  |
|---------------------------|----------------------|-----------------------------------|------|---------|------|------------------|
| AT24C1024E1               | TA = -40°C to +105°C |                                   |      |         |      |                  |
| AT24C1024E0               | TA = -40°C to +125°C |                                   |      |         |      |                  |
| Parameter                 | Symbol               | Min                               | Typ  | Max     | Unit | Condition        |
| Supply Voltage            | VCC1                 | 1.7                               | -    | 5.5     | V    | -                |
| Supply Current VCC=5.0V   | ICC1                 | -                                 | 0.26 | 0.5     | mA   | READ at 400KHZ   |
| Supply Current VCC=5.0V   | ICC2                 | -                                 | 0.28 | 0.5     | mA   | WRITE at 400KHZ  |
| Supply Current VCC=5.0V   | ISB1                 | -                                 | 0.03 | 0.5     | μA   | VIN=VCC or VSS   |
| Input Leakage Current     | IL1                  | -                                 | 0.10 | 1.0     | μA   | VIN=VCC or VSS   |
| Output Leakage Current    | ILO                  | -                                 | 0.05 | 1.0     | μA   | VOUT=VCC or VSS  |
| Input Low Level           | VIL1                 | -0.3                              | -    | VCC×0.3 | V    | VCC=1.7V to 5.5V |
| Input High Level          | VIH1                 | VCC×0.7                           | -    | VCC+0.3 | V    | VCC=1.7V to 5.5V |
| Output Low Level VCC=1.7V | VOL1                 | -                                 | -    | 0.2     | V    | IOL=2.1mA        |
| Output Low Level VCC=5.0V | VOL2                 | -                                 | -    | 0.4     | V    | IOL=3.0mA        |

Table 4

## Pin Capacitance

Applicable over recommended operating range from TA = 25°C, f = 1MHz, VCC = +5.0V

| Parameter                     | Symbol          | Min | Typ | Max | Unit | Condition           |
|-------------------------------|-----------------|-----|-----|-----|------|---------------------|
| Input/Output Capacitance(SDA) | C <sub>IO</sub> | -   | -   | 8   | pF   | V <sub>IO</sub> =0V |
| Input Capacitance(A1,A2,SCL)  | C <sub>IN</sub> | -   | -   | 6   | pF   | V <sub>IN</sub> =0V |

Table 5



## AC Electrical Characteristics

Applicable over recommended operating range from (unless otherwise noted):

| AT24C1024                                                     | TA =-40°C to +85°C  | VCC = +1.7V to +5.5V<br>CL=100 pF |     |     |                 |     |      |             |
|---------------------------------------------------------------|---------------------|-----------------------------------|-----|-----|-----------------|-----|------|-------------|
| AT24C1024E1                                                   | TA =-40°C to +105°C |                                   |     |     |                 |     |      |             |
| AT24C1024E0                                                   | TA =-40°C to +125°C |                                   |     |     |                 |     |      |             |
| Parameter                                                     | Symbol              | 1.7V≤VCC < 2.5V                   |     |     | 2.5V≤VCC < 5.5V |     |      | Units       |
|                                                               |                     | Min                               | Typ | Max | Min             | Typ | Max  |             |
| Clock Frequency,SCL                                           | fSCL                | -                                 | -   | 400 | -               | -   | 1000 | KHZ         |
| Clock Pulse Width Low                                         | tLOW                | 1.3                               | -   | -   | 0.5             | -   | -    | μs          |
| Clock Pulse Width High                                        | tHIGH               | 0.6                               | -   | -   | 0.26            | -   | -    | μs          |
| Noise Suppression Time                                        | tl                  | -                                 | -   | 50  | -               | -   | 50   | ns          |
| Clock Low to Data Out Valid                                   | tAA                 | -                                 | -   | 0.9 | -               | -   | 0.45 | μs          |
| Time the bus must be free before a new transmission can start | tBUF                | 1.3                               | -   | -   | 0.5             | -   | -    | μs          |
| Start Hold Time                                               | tHD:STA             | 0.6                               | -   | -   | 0.25            | -   | -    | μs          |
| Start Setup Time                                              | tSU:STA             | 0.6                               | -   | -   | 0.25            | -   | -    | μs          |
| Data In Hold Time                                             | tHD:DAT             | 0                                 | -   | -   | 0               | -   | -    | μs          |
| Data in Setup Time                                            | tSU:DAT             | 100                               | -   | -   | 100             | -   | -    | ns          |
| Input Rise Time(1)                                            | tR                  | -                                 | -   | 0.3 | -               | -   | 0.12 | μs          |
| Input Fall Time(1)                                            | tF                  | -                                 | -   | 0.3 | -               | -   | 0.12 | μs          |
| Stop Setup Time                                               | tSu:STO             | 0.6                               | -   | -   | 0.25            | -   | -    | μs          |
| Data Out Hold Time                                            | tDH                 | 50                                | -   | -   | 50              | -   | -    | ns          |
| Write Cycle Time                                              | tWR                 | -                                 | 3.5 | 5   | -               | 3.5 | 5    | ms          |
| 5.0V,25°C,Byte Mode(1)                                        | Endurance           | 4M                                | -   | -   | 4M              | -   | -    | Write Cycle |

Table 6

### Notes:

1. This parameter is characterized and is not 100% tested.
2. AC measurement conditions:  
 RL (connects to VCC): 1.3 k  
 Input pulse voltages: 0.3 VCC to 0.7 VCC  
 Input rise and fall time: 50 ns  
 Input and output timing reference voltages: 0.5 VCC  
 The value of RL should be concerned according to the actual loading on the user's system.



(131,072×8)Bus Timing




Figure 11. SCL: Serial Clock, SDA: Serial Data I/O

Write Cycle Timing




Figure 12. SCL: Serial Clock, SDA: Serial Data I/O

Notes:

The write cycle time  $t_{WR}$  is the time from a valid stop condition of a write sequence to the end of the internal clear/write cycle.








(131,072×8)Package

## Information

### SOP






COMMON DIMENSIONS  
(Unit of Measure=mm)

| SYMBOL | MIN     | NOM  | MAX  |
|--------|---------|------|------|
| A      | 1.35    | -    | 1.75 |
| A1     | 0.10    | -    | 0.23 |
| B      | 0.39    | -    | 0.48 |
| C      | 0.21    | -    | 0.26 |
| D      | 4.70    | 4.90 | 5.10 |
| E1     | 3.70    | 3.90 | 4.10 |
| E      | 5.80    | 6.00 | 6.20 |
| e      | 1.27BSC |      |      |
| L      | 0.50    | -    | 0.80 |
| Φ      | 0"      | -    | 8"   |




產品尺寸規格 (UNIT:mm)

| 規格 | W                                      | P1      | E         | F        | D0                                 | D1                                 | P0        | P2     | 10P0   |
|----|----------------------------------------|---------|-----------|----------|------------------------------------|------------------------------------|-----------|--------|--------|
| 尺寸 | 12.0 <sup>+0.30</sup> <sub>-0.10</sub> | 8.0±0.1 | 1.75±0.1  | 5.5±0.05 | 1.5 <sup>+0.10</sup> <sub>-0</sub> | 1.5 <sup>+0.25</sup> <sub>-0</sub> | 4±0.1     | 2±0.05 | 40±0.2 |
| 規格 | A0                                     | A1      | B0        | B1       | K0                                 | K1                                 | T         |        |        |
| 尺寸 | 6.40±0.10                              |         | 5.40±0.10 |          | 2.10±0.10                          |                                    | 0.25±0.03 |        |        |




B-B







TSSOP



Top View



Side View



End View

COMMON DIMENSIONS


Unit of Measure=mm

| SYMBOL | MIN     | NOM  | MAX  |
|--------|---------|------|------|
| D      | 2.90    | 3.00 | 3.10 |
| E      | 6.20    | 6.40 | 6.60 |
| E1     | 4.30    | 4.40 | 4.50 |
| A      | -       | -    | 1.20 |
| A1     | 0.05    | -    | 0.15 |
| b      | 0.21    | -    | 0.30 |
| e      | 0.65BSC |      |      |
| L      | 0.45    | 0.60 | 0.75 |
| L1     | 1.00REF |      |      |






(131,072×8)UDFN





## WLCSP



## Ordering information

| Order Number            | Packag<br>e | Package Quantity | Marking<br>On The park |
|-------------------------|-------------|------------------|------------------------|
| AT24C1024BN-SH25-T-TUDI | SOP8        | Tape,Reel,2500   | 1024B25                |



## Important statement:

- TUDI Semiconductor reserves the right to modify the product manual without prior notice! Before placing an order, customers need to confirm whether the obtained information is the latest version and verify the completeness of the relevant information.
- Any semi-guide product is subject to failure or malfunction under specified conditions. It is the buyer's responsibility to comply with safety standards when using TUDI Semiconductor products for system design and whole machine manufacturing. And take the appropriate safety measures to avoid the potential in the risk of loss of personal injury or loss of property situation!
- TUDI Semiconductor products have not been licensed for life support, military, and aerospace applications, and therefore TUDI Semiconductor is not responsible for any consequences arising from the use of this product in these areas.
- If any or all TUDI Semiconductor products (including technical data, services) described or contained in this document are subject to any applicable local export control laws and regulations, they may not be exported without an export license from the relevant authorities in accordance with such laws.
- The specifications of any and all TUDI Semiconductor products described or contained in this document specify the performance, characteristics, and functionality of said products in their standalone state, but do not guarantee the performance, characteristics, and functionality of said products installed in Customer's products or equipment. In order to verify symptoms and conditions that cannot be evaluated in a standalone device, the Customer should ultimately evaluate and test the device installed in the Customer's product device.
- TUDI Semiconductor documentation is only allowed to be copied without any alteration of the content and with the relevant authorization. TUDI Semiconductor assumes no responsibility or liability for altered documents.
- TUDI Semiconductor is committed to becoming the preferred semiconductor brand for customers, and TUDI Semiconductor will strive to provide customers with better performance and better quality products.