

Data Sheet

RF TERMINATION Type 65_MMCX-50-0-31

Description

Standard Termination, Low Power



Product Configuration

Connector	MMCX jack (female)
Interface standards	HUBER+SUHNER - MMCX

Technical Data

Electrical Data

Nominal Impedance	50 Ω
Frequency range	0 to 3 GHz
VSWR max.	1.22
Power rating	0.5 Watt average power up to 30 °C ambient temperature, linearly derated to 0 Watt at 85 °C ambient temperature.

Mechanical Data

Weight	0.0014 kg
--------	-----------

Environmental Data

Operating temperature 2011/65/EU (RoHS)	-55 °C to 85 °C compliant
--	------------------------------

Material Data

Piece Part	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Brass	Gold Plating (without Nickel underplating)
Body	Brass	Gold Plating (without Nickel underplating)
Insulator	PFA / PTFE	

Related Documents

Outline drawing	DOU-00008667
-----------------	--------------

Ordering Information

Single Packaging Packaging	65_MMCX-50-0-31/111_OE
-------------------------------	------------------------

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[HUBER+SUHNER:](#)

[65_MMCX-50-0-31/111_OE](#)