



SPECIFICATIONS

- 1、Current Rating: 1A AC, DC
- 2、Voltage Rating: 125V AC, DC
- 3、Temperatuer Range: -25°C~+85°C
- 4、Contact Resistance: 20mΩ Max
- 5、Insulation Resistance: 100MΩ Min
- 6、Withstanding Voltang: 500V AC/minute
- 7、Material: Nylo66, UL94V-0

编 号	尺寸 (mm)	
	A	B
A1251-02Y	1.25	4.25
A1251-03Y	2.50	5.50
A1251-04Y	3.75	6.75
A1251-05Y	5.00	8.00
A1251-06Y	6.25	9.25
A1251-07Y	7.50	10.50
A1251-08Y	8.75	11.75
A1251-09Y	10.00	13.00
A1251-10Y	11.25	14.25
A1251-11Y	12.50	15.50
A1251-12Y	13.75	16.75
A1251-20Y	23.75	26.75

制图 DRAWN	变更内容 DESCRIPTION	日期 DATE	GENERAL TOLERANCE		制图 DRAWING	黄彬		料号 PART NO.	HX 1.25-8Y		版本 REV.	A
			X.±0.25	X.*±2'		张伟		品名 TITLE	压线端子胶壳		页次 SHEET	1/1
			.XX±0.20	.X'±1'	审核 CHECK	罗小春		客户料号 CUTM. NO.				
			.XX±0.15	.XX'±0.5'	核准 APPROVAL					深圳市韩下电子有限公司		
			.XXX±0.10	.XXX'±0.5'	单位 UNITS	MM	比例	1:1				