




LEFT SIDE VIEW





FRONT VIEW




BOTTOM VIEW



RIGHT SIDE VIEW

RECOMMENDED PCB LAYOUT
VIEWED FROM COMPONENT SIDE

TOP VIEW




BACK VIEW

XKB Connectivity

Electrical 电气:

- Turn ratio 匝数比: 1~2: J1~J2=1CT:1CT(±2%)
3~4: J3~J6=1CT:1CT(±2%)
7~8: J4~J5=1CT:1CT(±2%)
9~10: J7~J8=1CT:1CT(±2%)
- OCL: 350uH Min at 100KHz 100mV 8mA DC.
- Insertion Loss 插入损耗: -1.0 dB Max 1~100MHz.
- Return loss 回程损耗: -18dB Min 1~30MHz
-14dB Min 30~60MHz
-12dB Min 60~80MHz
-10dB Min 80~100MHz
- Cross talk 声道串扰: -40dB Min 1~30MHz;
-35dB Min 30~60MHz;
-30dB Min 60~100MHz;
- CMR 共模抑制: -30dB Min 1~100MHz;
- Hi-Pot 耐压测试: 1500V AC & 2250V DC 6S
1mA PRI TO SEC



XKB Connectivity

MATERIAL 材料:

HOUSING 外壳: PBT, UL94V-0, BLACK. HF
TERMINALS BRACKET 端子支架: PBT, UL94V-0, BLACK. HF
SHIELD 保护物: C2680, T=0.20MM, NICKEL PLATING ON ALL AREA.
TERMINAL 端子: PHOSPHOR BRONZE C5210, T=0.35MM,
GOLD PLATING ON CONTACT AREA.

MECHANICAL 机械:

DURABILITY 耐用性: 750 CYCLES MIN.
MATING FORCE 配合力: 23N MAX.
OPERATING TEMPERATURE 工作温度: -40°C~+85°C.
STORAGE TEMPERATURE 储存温度: -40°C~+85°C.
ALL CRITICAL DIMENSIONS WITH "MM"

DSND		SCALE: N/A	MODEL TYPE:		
DWN		VIEW: 	RJ JACK		
CHKD		UNIT: mm/in	PART NO.:		
APPD		SIZE: A4	DWG NO.:		
			X01AQ070HWDD		
PRECISION CO.,LIMITED			WEIGHT	SHEET	REVISIO
				1/1	A0

XKB

XKB INDUSTRIAL PRECISION CO., LIMITED

广东星坤科技股份有限公司

ΔX		日期
ΔX		
ΔX		
MARK		DESCRIPTION

文件工程章

REVISIONS	DATE	REVISED	APPROVED
UNSPECIFIED TOLERANCES			

www.helloxkb.com www.helloxkb.cn www.xk-dg.cn