

Product Summary

$V_{(BR)DSS}$	$R_{DS(on)TYP}$	I_D
40V	4.5mΩ@10V	75A
	6.5mΩ@4.5V	



合肥矽普半导体

Siliup Semiconductor Technology Co., Ltd

技术 品质 服务

www.siliup.com


Feature

- Fast switching speed
- Surface mount package
- ROHS Compliant & Halogen-Free
- 100% Single Pulse avalanche energy Test

Applications


- DC-DC Converters.
- Motor Control.

Package



PDFN5X6-8L

Circuit diagram



Marking



SP40N04NK
**

:Device Code
:Week Code

Order Information

Device	Package	Unit/Tape
SP40N04NK	PDFN5X6-8L	5000

Absolute maximum ratings (Ta=25°C, unless otherwise noted)

Parameter	Symbol	Rating	Unit
Drain-Source Voltage	V_{DS}	40	V
Gate-Source Voltage	V_{GS}	± 20	V
Continuous Drain Current (Tc=25°C)	I_D	75	A
Continuous Drain Current (Tc=100°C)	I_D	50	A
Pulse Drain Current Tested	I_{DM}	300	A
Single pulsed avalanche energy ¹	E_{AS}	156	mJ
Power Dissipation (Tc=25°C)	P_D	65	W
Thermal Resistance Junction-to-Case	$R_{\theta JC}$	1.9	°C/W
Storage Temperature Range	T_{STG}	-55 to 150	°C
Operating Junction Temperature Range	T_J	-55 to 150	°C


Electrical characteristics (Ta=25°C, unless otherwise noted)

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Static Characteristics						
Drain-Source Breakdown Voltage	BV _{DSS}	VGS=0V , ID=250uA	40	-	-	V
Drain-Source Leakage Current	IDSS	VDS=32V , VGS=0V , TJ=25℃	-	-	1	uA
Gate-Source Leakage Current	IGSS	VGS=±20V , VDS=0V	-	-	±100	nA
Gate Threshold Voltage	VGS(th)	VGS=VDS , ID =250uA	1.2	1.6	2.5	V
Static Drain-Source On-Resistance	RDS(ON)	VGS =10V, ID =10A	-	4.5	6	mΩ
		VGS =4.5V, ID =6A	-	6.5	10	
Dynamic characteristics						
Input Capacitance	Ciss	VDS=20V , VGS=0V , f=1MHz	-	3785	-	pF
Output Capacitance	Coss		-	285	-	
Reverse Transfer Capacitance	Crss		-	256	-	
Total Gate Charge	Qg	VDS=20V , VGS=10V , ID=30A	-	71	-	nC
Gate-Source Charge	Qgs		-	15.3	-	
Gate-Drain Charge	Qgd		-	14.5	-	
Switching Characteristics						
Turn-On Delay Time	Td(on)	VDD=20V VGS=10V , RG=3Ω, ID=30A	-	12	-	nS
Rise Time	Tr		-	28	-	
Turn-Off Delay Time	Td(off)		-	63	-	
Fall Time	Tf		-	12	-	
Diode Characteristics						
Diode Forward Voltage	VSD	VGS=0V , IS=1A , TJ=25℃	-	-	1.2	V
Maximum Body-Diode Continuous Current	IS		-	-	75	A
Reverse recover time	Trr	IS=20A, di/dt=100A/us, TJ=25℃	-	17	-	nS
Reverse recovery charge	Qrr		-	9	-	nC


Note:

- The EAS Test condition is $V_{DD}=30V, V_{GS}=10V, L=0.1mH, R_G=25\Omega$


Typical Characteristics




Output Characteristics




Transfer Characteristics




Capacitance Characteristics




Gate Charge




Current dissipation




Power dissipation




RDS(on) VS Drain Current




Forward characteristics of reverse diode




Normalized breakdown voltage



Normalized Threshold voltage




Maximum Transient Thermal Impedance




Safe Operation Area


PDFN5X6-8L Package Information



Top View
[顶视图]



Bottom View
[背视图]



Side View
[侧视图]

Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	0.900	1.000	0.035	0.039
A3	0.254REF.		0.010REF.	
D	4.944	5.096	0.195	0.201
E	5.974	6.126	0.235	0.241
D1	3.910	4.110	0.154	0.162
E1	3.375	3.575	0.133	0.141
D2	4.824	4.976	0.190	0.196
E2	5.674	5.826	0.223	0.229
k	1.190	1.390	0.047	0.055
b	0.350	0.450	0.014	0.018
e	1.270TYP.		0.050TYP.	
L	0.559	0.711	0.022	0.028
L1	0.424	0.576	0.017	0.023
H	0.574	0.726	0.023	0.029
θ	10°	12°	10°	12°