

REVISIONS					
REV.	ECN NO.	LOCATION	DESCRIPTION	DATE	DESIGN
A2	N/A		产品总长尺寸修正	2024.08.20	阿树
A3	N/A		产品电气性能	2025.12.22	阿树

SPECIFICATIONS
Voltage rating:500V AC/DC
Rated Current:2AMP
Withstand Voltage:500V AC/DC
Contact Resistance:20mΩ Max
Insulation Resistance:1000MΩ Min
Operation Temperature:−40°C~+125°C
Contact Material:Phosphor Bronze
Contact Plating:Au Plating and Over Ni
Insulator Material:Polyester(UL94V-0)
Standard: PA6T
Max.Processing Temp: 230°C for 30–60 seconds
(260°C for 10 seconds)

PART NO.:
X4611 F V S-08-C43 D45 R2
① ② ③ ④ ⑤ ⑥ ⑦ ⑧

- ① Series No.
② Category:T–Terminal
③ Welding Board Angle:V–Stright 180°
④ Welding Way:S–SMT
⑤ Row No.Pin No:XX–02~40Pin
⑥ Plastic Height:C=4.3mm
⑦ Pin pitch:D=4.5mm
⑧ Type:R1 ; R2

X4611FVS-08-C43D45R2	PA6T	Brass	X4611W
PART NO	Material	Wire Range	Suitable XKB Wafer
DESIGN	阿树	VIEW: 	MODEL TYPE: 2.0mm BTB Connector
CHECKED		UNIT: mm/in	PART NO.: X4611FVS-08-C43D45R2
APPROVED		SIZE: A4	DWG NO.: X-X4611FVS-08-C43D45R2
SCALE			PAGE
N/A			1/1
REVISION			A3

AuGLAR	±5°
X.	±0.40
X.x	±0.30
X.xx	±0.20
X.xxx	±0.15
UNSPECIFIED TOLERANCES	



XKB INDUSTRIAL PRECISION CO.,LIMITED