

DisplayPort KVM Cable Kit - DP, USB, 3.5 mm  
Audio (3xM/3xM) + USB (M/M), 4K, 4:4:4, 6 ft.  
(1.83 m), Black

MODEL NUMBER: P783-006-U



DisplayPort KVM cable kit with DisplayPort, USB A/B and 3.5 mm plugs connects your computer to a Tripp Lite B002-HD1AC4 or other compatible NIAP KVM.

Features

**6 ft. Cables Connect Your DisplayPort Computer to a NIAP KVM Switch with CAC**This DisplayPort cable kit includes two 6-ft. (1.83 m) cables for connecting a computer to a KVM switch with a Common Access Card (CAC) port. The P783-006 features DisplayPort, USB A/B and 3.5 mm audio connectors on both ends for connecting your computer to a KVM switch. The U022-006 is a USB cable that connects to the KVM's CAC port for accessing smart cards, scanners and biometric readers, including fingerprint readers, to bolster security.

**Specifically Designed for Select KVMs to Save You Time and Money**Recommended for the B002-HD1AC4 or other compatible NIAP KVM. The DisplayPort cable supports video resolutions up to 3840 x 2160 (4K x 2K) at 60 Hz with true 4:4:4 chroma subsampling. The USB cables also support USB 2.0 data transfer speeds up to 480 Mbps. By combining several different cables into one convenient kit, you cut down on unnecessary clutter and costs.

Highlights

- Cuts cable clutter and saves money by combining essential KVM cables into just 2
- 6-ft. (1.83 m) 3-in-1 DP, USB A/B and 3.5 mm audio cable connects KVM to your computer
- Delivers UHD picture quality at resolutions up to 3840 x 2160 (4K x 2K) @ 60 Hz
- Supports true 4:4:4 chroma subsampling to meet latest color standards
- 6-ft. (1.83 m) USB A/B cable included for KVM's CAC port (smart cards, scanners, etc.)

Applications

- Connect a headless computer to a Tripp Lite KVM switch with CAC support
- Upgrade or replace worn or lost KVM cables
- Eliminate clutter and save money by replacing multiple cables with one new kit
- Extend the distance between the KVM switch and computer to 6-ft. (1.83 m)

System Requirements

- B002-HD1AC4 NIAP KVM or other compatible KVM switch

Package Includes

- P783-006 DisplayPort KVM cable kit, 3 in 1 (M/M), 6-ft. (1.83 m)
- U022-006 USB A/B cable (M/M), 6-ft. (1.83 m)

Specifications

| OVERVIEW        |                        |
|-----------------|------------------------|
| UPC Code        | 037332241658           |
| Accessory Type  | Cable Kit              |
| Technology      | DisplayPort            |
| Accessory Class | KVM Switch Accessories |

| VIDEO                           |                                                |
|---------------------------------|------------------------------------------------|
| Max Supported Video Resolution  | 3840 x 2160 @ 60Hz                             |
| PHYSICAL                        |                                                |
| Color                           | Black                                          |
| Cable Jacket Color              | Black                                          |
| Cable Length (ft.)              | 6                                              |
| Cable Length (m)                | 1.83                                           |
| Cable Length (in.)              | 72                                             |
| Shipping Dimensions (hwd / in.) | 1.00 x 8.00 x 10.75                            |
| Shipping Dimensions (hwd / cm)  | 2.54 x 20.32 x 27.30                           |
| Shipping Weight (lbs.)          | 0.66                                           |
| Shipping Weight (kg)            | 0.30                                           |
| Unit Dimensions (hwd / in.)     | 1.000 x 8.000 x 10.750                         |
| ENVIRONMENTAL                   |                                                |
| Operating Temperature Range     | 14° to 122°F (-10° to 50°C)                    |
| Storage Temperature Range       | 5° to 140°F (-15° to 60°C)                     |
| Relative Humidity               | 0 ~ 90% RH, Non-Condensing                     |
| CONNECTIONS                     |                                                |
| Side A - Connector 1            | 3.5MM (MALE); DISPLAYPORT (MALE); USB A (MALE) |
| Side A - Connector 2            | USB A (MALE)                                   |
| Side B - Connector 1            | 3.5MM (MALE); DISPLAYPORT (MALE); USB B (MALE) |
| Side B - Connector 2            | USB B (MALE)                                   |
| Contact Plating                 | Gold                                           |
| FEATURES & SPECIFICATIONS       |                                                |
| USB Specification               | USB 2.0 (up to 480 Mbps)                       |
| Displayport Specification       | 1.2                                            |
| HDCP Specification              | 2.2                                            |
| STANDARDS & COMPLIANCE          |                                                |
| Product Compliance              | RoHS                                           |
| WARRANTY & SUPPORT              |                                                |



1000 Eaton Boulevard  
Cleveland, OH 44122  
United States

|                                        |                           |
|----------------------------------------|---------------------------|
| Product Warranty Period<br>(Worldwide) | Lifetime limited warranty |
|----------------------------------------|---------------------------|



© 2023 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.