



▼ Heatsinks f.cool

- ▼ Profile heatsinks and fluid coolers
  - [Standard extruded heatsinks](#)
  - Extruded heatsinks for lock-in retaining spring
  - Extruded heatsinks for PCB mounting
  - Extruded heatsinks for DC/DC converter
  - Retaining springs for transistors
  - U-Extruded heatsinks
  - Die-cast heatsinks
  - Fin coolers
  - Fluid coolers
  - Aluminium flat-, quadrangular-, angled-, U- and T-profiles
- ▶ Heatsinks and active heatsinks for processors
- ▶ Board Level heatsinks
- ▶ Cooling aggregates
- ▶ Accessories for electronic components

▶ Cases f.case

▶ Connectors f.con

## Standard extruded heatsinks

### SK 456 ...

#### SK 456 100 SA

40 x 6 mm, for pcb mounting SK 456 ... x M3 L

Data sheet

add to request



Features

Technical Drawing

Service

Accessories / related products

|                                               |                |
|-----------------------------------------------|----------------|
| <b>thermal resistance <math>R_{th}</math></b> | 15.1 - 9.1 K/W |
| <b>surface</b>                                | black anodised |
| <b>height</b>                                 | 6 mm           |
| <b>width B</b>                                | 40 mm          |
| <b>length</b>                                 | 100 mm         |
| <b>plate thickness</b>                        | 1.8 mm         |