



CONNECTORS

CONNECTOR HOUSINGS



✓ Active

TE CONNECTIVITY (TE)

HOUSING.

AMP

826884-3

TE Internal Number: 826884-3

EU RoHS Compliant

EU ELV Compliant

Connector System Wire-to-Wire

Connector Style Housing for female terminals

Centerline (Pitch) (in) .138

Number of Positions 2

Pitch (mm) 3.5

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**

DOCUMENTATION

Product Drawings

2 Pol Econoseal Serie E Buchsengehäuse Assembled

PDF

English

CAD Files

Customer View Model

2D_DXF.ZIP

English

3D PDF

PDF

3D

Customer View Model

3D_IGS.ZIP

English

Customer View Model

3D_STP.ZIP

English

FEATURES



Please review product documents or [contact us](#) for the latest agency approval information.

Please Note: Use the Product Drawing for all design activity.

Product Type Features

Connector System Wire-to-Wire

Connector Style Housing for female terminals

Sealed Yes

Hybrid Connector No

Primary Locking Feature On the terminal

Strain Relief No

Configuration Features

Number of Positions 2

Electrical Characteristics

Nominal Voltage Architecture (V) 12

Operating Voltage (VAC) 12

Body Features

Color Black

Cable Exit Angle 180°

Body Material PA GF

Mechanical Attachment

Mounting Feature No

Terminal Position Assurance No

Polarized Yes

Housing Features

Centerline (Pitch) (in) .138

Pitch (mm) 3.5

Dimensions

Width 30.5 mm [1.201 in]

Height 19 mm [.748 in]

Length 19 mm [.748 in]

Usage Conditions

Operating Temperature (Max) (°C) 70, 75, 80, 85, 90, 100, 105, 110, 120

Operating Temperature (Max) (°F) 158, 167, 176, 185, 194, 212, 221, 230, 248

Operating Temperature Range -40 – 120 °C [-40 – 248 °F]

Industry Standards

Degree of Protection Other

Packaging Features

Packaging Method Box

Packaging Quantity 1500

Other

Connector Position Assurance Capable No

Serviceable No

Statement of Compliance

Statement of Compliance

PDF