

REVISIONS					
REV.	ECN NO.	LOCATION	DESCRIPTION	DATE	DESIGN
A0	N/A		INITIAL RELEASE	/	/
A1	N/A		图面升级整理图面	2025.2.8	阿树

Specifications:
规格:
Voltage rating:400V AC/DC
额定电压: 400V AC/DC
Current rating:10A AC/DC
额定电流: 10A AC/DC
Withstanding voltage:1800V AC/minute
耐受电压: 1800V AC/分钟
Temperature range:-40℃--+105℃
温度范围: -40℃--+105℃
Insulation resistance:100MΩ min
绝缘电阻: 100MΩ Min
Contact resistance:10mΩ Max
接触电阻: 10mΩ Max

PART NO.:
X2513 I-H V01-H
① ② ③ ④ ⑤
①Series Number.
②Category: T-terminal
③Material:H-High conductivity copper alloy
④Plating Category:V01-Gold Flash;
V01-Gold Flash Plating
⑤Special No:H-High foot for #20~22AWG
L-Low foot for #24~26AWG

PART NO	Wire range	DIM.A	DIM.B	DIM.C	DIM.D
X2513T-HSN-H	#20~#22	1.50	2.15	2.00	2.15
X2513T-HSN-L	#24~#26	1.40	2.15	2.00	1.45
X2513T-HV01-H	High conductivity copper alloy	#20~#26		X2513H	
PART NO	Material	Wire range		Suitable XKB Housing	

AuGLAR	±5°
X.	±0.40
X.x	±0.30
X.xx	±0.20
X.xxx	±0.15
UNSPECIFIED TOLERANCES	



DESIGN	阿树	VIEW:		MODEL TYPE:	2.50mm Crimp Style Connector
CHECKED		UNIT:	mm/in	PART NO.:	X2513T-HV01-H
APPROVED		SIZE:	A4	DWG NO.:	X-X2513T-HV01-H

XKB INDUSTRIAL PRECISION CO.,LIMITED

SCALE	PAGE	REVISION
N/A	1/1	A1

A

A

B

B

C

C

D

D