

1		2		3		4		5		6		7		8													
SAMZO		REAC/ROHS								REV	ECN NO	DESRIPTION	DESIGN	APPROVAL	DATE												
										A1	NEW	Replace frame			2018.06.12												
E	主要技术参数、性能 The Main Thchnology Performance																										
	<table><tr><td>额定电流、电压 Rate voltage,current</td><td>50mA DC12V</td></tr><tr><td>接触电阻 Contact resistance</td><td>≤100mΩ</td></tr><tr><td>按力 Operating force</td><td>±50gf</td></tr><tr><td>行程 Travel</td><td>0.2±0.10mm</td></tr><tr><td>绝缘电阻 Insulated resistance</td><td>≥100MΩ</td></tr><tr><td>介电强度 Dielectric strength</td><td>≥250VAC/1min</td></tr></table>															额定电流、电压 Rate voltage,current	50mA DC12V	接触电阻 Contact resistance	≤100mΩ	按力 Operating force	±50gf	行程 Travel	0.2±0.10mm	绝缘电阻 Insulated resistance	≥100MΩ	介电强度 Dielectric strength	≥250VAC/1min
	额定电流、电压 Rate voltage,current	50mA DC12V																									
	接触电阻 Contact resistance	≤100mΩ																									
按力 Operating force	±50gf																										
行程 Travel	0.2±0.10mm																										
绝缘电阻 Insulated resistance	≥100MΩ																										
介电强度 Dielectric strength	≥250VAC/1min																										
D	爆炸图																										
	尺寸图																										
	电路原理图																										
	PCB. 焊接图																										
C	物料清单																										
	技术参数																										
	规格书																										
	认证																										
B	公司简介																										
	联系我们																										
	售后服务																										
	法律声明																										
A	联系我们																										
	售后服务																										
	法律声明																										
	联系我们																										