

FEATURES

Low Forward Voltage Drop

Very Small SMD Package

APPLICATIONS

Low Voltage Rectification

High Efficiency DC/DC Conversion

Switch Mode Power Supply

Inverse Polarity Protection

Low Power Consumption Applications

SOD-323



ELECTRICAL CHARACTERISTICS(T_a=25°C unless otherwise specified)

Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
Reverse breakdown voltage	V _(BR)	I _R =1mA	20			V
Reverse current	I _R	V _R =10V			80	μA
		V _R =20V			100	
Forward voltage	V _F *	I _F =1A			0.45	V
		I _F =2A			0.55	
Total capacitance	C _{tot}	V _R =4V,f=1MHz			120	pF

*Pulse test: t_p ≤ 300 μs; δ ≤ 0.02.





MAXIMUM RATINGS (T_a=25°C unless otherwise noted)


Symbol	Parameter	Value	Unit
V _{RRM}	Peak Repetitive Reverse Voltage	20	V
V _{RWM}	Working Peak Reverse Voltage		
V _{R(RMS)}	RMS Reverse Voltage	14	V
I _F	Continuous Forward Current	2	A
I _{FSM}	Non-repetitive Peak Forward Surge Current @ t=8.3ms	9	A
P _D	Power Dissipation	Note1 250	mW
		Note2 480	
R _{JA}	Thermal Resistance from Junction to Ambient	Note1 400	°C/W
		Note2 208	
T _j	Operating Junction Temperature Range	-40 ~ +125	°C
T _{stg}	Storage Temperature Range	-55 ~ +150	°C

1:Device mounted on an FR4 PCB, single-sided copper, tin-plated and standard footprint.


2.Device mounted on an FR4 PCB with copper pad 10 x 10 mm.

Typical Characteristics



SOD-323 Package Outline Dimensions


Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A		1.100		0.043
A1	0.000	0.100	0.000	0.004
A2	0.800	1.000	0.031	0.039
b	0.250	0.350	0.010	0.014
c	0.080	0.150	0.003	0.006
D	1.200	1.400	0.047	0.055
E	1.600	1.800	0.063	0.071
E1	2.500	2.750	0.098	0.108
L	0.475 REF		0.019 REF	
L1	0.250	0.400	0.010	0.016
θ	0°	8°	0°	8°

SOD-323 Suggested Pad Layout

Note:

1. Controlling dimension: in millimeters.
2. General tolerance: $\pm 0.05\text{mm}$.
3. The pad layout is for reference purposes only.