

1N5819WT

DATASHEET


Specification Revision History:

Version	Date	Description
V1.0	2021/06	New
V1.1	2023/05	Modify Ordering Information
V1.2	2024/02	Modify Ordering Information
V1.3	2025/05	Add application precautions and overall typesetting.

FEATURES

- ※ Schottky Barrier Rectifiers
- ※ Low Forward Voltage Drop
- ※ Fast Switching Time
- ※ Surface Mount Package Ideally Suited for Automated Insertion
- ※ Lead, Halogen and Antimony Free, RoHS Compliant "Green" Device

TOP VIEW AND PINNING



1、Cathode

2、Anode

SOD-523

ORDERING INFORMATION

Product Model	Package Type	Packing	Packing Qty
1N5819WT(GMIC)	SOD-523	REEL	3000PCS/REEL
1N5819WT	SOD-523	REEL	3000PCS/REEL

MAXIMUM RATINGS (Ta=25°C unless otherwise noted)

Parameter	Symbol	Value	Unit
Repetitive Peak Reverse Voltage	V_{RRM}	40	V
RMS Reverse Voltage	$V_{R(RMS)}$	28	V
Working Peak Reverse Voltage	V_{RWM}	40	V
DC Blocking Voltage	V_R	40	V
Forward Current	I_F	200	mA
Non-Reptitive Peak Forward Surge Current at t=8.3ms	I_{FSM}	0.5	A
Power Dissipation	P_D	200	mW
Operating Temperature Range	T_J	-55 to 125	°C
Storage Temperature Range	T_{stg}	-55 to 150	°C

ELECTRICAL CHARACTERISTICS (TA=25°C unless otherwise noted)

Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
Breakdown Voltage	V_{BR}	$I_R=100\mu A$	40			V
Forward Voltage	V_{F1}	$I_F=1mA$		0.27		V
	V_{F2}	$I_F=5mA$		0.32		
	V_{F3}	$I_F=20mA$			0.37	
	V_{F4}	$I_F=200mA$			0.6	
Reverse Leakage Current	I_R	$V_R=30V$			5	μA
Junction Capacitance	C_j	$V_R=0V, f=1MHz$			28	pF

TYPICAL PERFORMANCE CHARACTERISTICS

Fig.1 Power Derating Curve




Fig.2 Typical Instantaneous Reverse Characteristics




Fig.3 Typical Forward Characteristic









Fig.4 Typical Junction Capacitance



OUTLINE DIMENSIONS

SOD-523



Symbol	Dimensions In Millimeters		Dimensions In Mil	
	Min	Max	Min	Max
A	0.51	0.77	20	30
e	0.25	0.35	10	14
C	0.08	0.15	3	6
D	1.10	1.30	43	51
E	0.75	0.99	30	39
HE	1.50	1.70	59	67
N	0.35 ref		14 ref	
L	0.2 ref		8.0 ref	
P	R0.1 ALL ROUND		R4.0 ALL ROUND	
∠	10°±1°			

IMPORTANT NOTICE

- Green Micro chip reserves the right to change products and documents without notice. Customers should obtain and verify the completeness of the latest technical information before placing orders. Meanwhile, Green Micro chip shall not assume any responsibility or obligation for non-officially revised documents.
- Any parameters in the entire product specification are for reference only, and actual application testing shall prevail. When customers use the products for system design, they must comply with safety regulations and independently assume the following responsibilities: selecting suitable Green Micro chip products according to application requirements; completing design verification and full-link testing of the application; and ensuring that the application complies with safety regulations or other requirements of the target market. Customers shall bear all personal or property losses caused by design defects or illegal operations, which shall have no relation to Green Micro chip.
- Green Micro chip products are prohibited from being used in scenarios such as life support, military equipment, and key aerospace applications. All accidents and legal liabilities arising from out-of-scope use shall be borne by the user, and Green Micro chip shall not be held responsible.
- All technical resources of Green Micro chip (including data sheets and reference designs) are provided "as is", without guarantee of no defects or universality, and without any express or implied warranties. The documents are only authorized for product development and research described in this document. Unauthorized use of intellectual property, public reproduction, and reverse engineering are strictly prohibited. All claims and losses caused by illegal use shall be borne by the user, and Green Micro chip shall not be liable.