

SACC-DSI-M8FS-3CON-M10-L180 SH - Device
connector rear mounting

1456116
<https://www.phoenixcontact.com/us/products/1456116>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Device connector rear mounting, 3-position, Socket, straight, M8, Rear mounting, M10, Solder pins

Your advantages

- Easy PCB assembly: one-piece connectors for wave soldering
- Standard pin assignments and codings for signal transmission with a uniform design-in design
- For high transmission reliability: optional shield connection to the housing and latching on the PCB

Commercial data

Item number	1456116
Packing unit	20 pc
Minimum order quantity	20 pc
Sales key	AB22
Product key	ABQJAB
Catalog page	Page 229 (C-2-2013)
GTIN	4046356605878
Weight per piece (including packing)	6.71 g
Weight per piece (excluding packing)	6.415 g
Customs tariff number	85366990
Country of origin	DE

SACC-DSI-M8FS-3CON-M10-L180 SH - Device connector rear mounting



1456116

<https://www.phoenixcontact.com/us/products/1456116>

Technical data

Mounting

Mounting type	Rear mounting M10 With flat nut
Assembly note	With flat nut

Product properties

Product type	Circular connectors (device side)
Number of positions	3
Shielded	yes
Coding	A
Thread type	M8

Data management status

Article revision	03
------------------	----

Insulation characteristics

Overvoltage category	II
Degree of pollution	3

Material specifications

Flammability rating according to UL 94	HB
Seal material	FKM
Contact material	Cu alloy
Contact surface material	Au
Contact carrier material	PA 6.6
Material for screw connection	Zinc die-cast, nickel-plated

Electrical properties

Rated surge voltage	1.5 kV
Contact resistance	$\leq 3 \text{ m}\Omega$
Insulation resistance	$\geq 100 \text{ M}\Omega$
Nominal voltage U_N	48 V AC
	60 V DC
Nominal current I_N	4 A

Connection data

Conductor connection

Connection method	Solder pins
Contact connection type	Socket
Tightening torque	1 Nm ... 1.5 Nm (Installation-side)

Mechanical properties

SACC-DSI-M8FS-3CON-M10-L180 SH - Device connector rear mounting



1456116

<https://www.phoenixcontact.com/us/products/1456116>

Mechanical data

Insertion/withdrawal cycles	> 100
-----------------------------	-------

Connector

Connection 1

Head design	Socket
Head cable outlet	straight
Head thread type	M8

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP67
	IP67
Ambient temperature (operation)	-40 °C ... 85 °C

Standards and regulations

M8

Standard designation	M8 connector
Standards/specifications	IEC 61076-2-104

SACC-DSI-M8FS-3CON-M10-L180 SH - Device connector rear mounting




1456116

<https://www.phoenixcontact.com/us/products/1456116>

Drawings

Schematic diagram



Pin assignment M8 socket, 3-pos., view female side

SACC-DSI-M8FS-3CON-M10-L180 SH - Device connector rear mounting



1456116
<https://www.phoenixcontact.com/us/products/1456116>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1456116>

 cUL Recognized Approval ID: E221474-20070307				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	30 V	4 A	24 - 24	-

 UL Recognized Approval ID: E221474-20070307				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	30 V	4 A	24 - 24	-

cULus Recognized				
-------------------------	--	--	--	--

SACC-DSI-M8FS-3CON-M10-L180 SH - Device connector rear mounting



1456116

<https://www.phoenixcontact.com/us/products/1456116>

Classifications

ECLASS

ECLASS-11.0	27440102
ECLASS-12.0	27440116
ECLASS-13.0	27440116

ETIM

ETIM 9.0	EC002635
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

1456116
<https://www.phoenixcontact.com/us/products/1456116>

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes
Exemption	6(c)
China RoHS	
Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	a50d6be5-7984-4c48-9f25-1e72f53f03f3

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com