

Pitch: 1.27x1.27mm(0.05" x 0.05") 0.40 SQ Pin
 Pin Header Board Spacer Dual Row S.M.T Type



Specifications

Current Rating: 1.0 Ampere
 Insulation Resistance: 1000MΩ Min
 Dielectric Withstanding: 300V AC
 Contact Resistance: 20mΩ Max
 Operating Temperature: -40°C to +105°C

Materials

Contact Material: Brass
 Insulation Material: Polyester, UL 94V-0
 LCP/NL6T

All material RoHS&Reach Compliant
 Halogen-free is available



Mating with



HFIDS44



HFIDM44



HFIDR43



HFIDM20



HFIDR52



HFIDM52

No. of Pins/Row	Dimension Information			No. of Pins/Row	Dimension Information			No. of Pins/Row	Dimension Information			No. of Pins/Row	Dimension Information		
	D	B	C		D	B	C		D	B	C		D	B	C
-	-	-	-	12	13.97	15.24	12.70	22	26.67	27.94	25.40	32	39.37	40.64	38.10
03	2.54	3.81	1.27	13	15.24	16.51	13.97	23	27.94	29.21	26.67	33	40.64	41.91	39.37
04	3.81	5.08	2.54	14	16.51	17.78	15.24	24	29.21	30.48	27.94				
05	5.08	6.35	3.81	15	17.78	19.05	16.51	25	30.48	31.75	29.21				
06	6.35	7.62	5.08	16	19.05	20.32	17.78	26	31.75	33.02	30.48				
07	7.62	8.89	6.35	17	20.32	21.59	19.05	27	33.02	34.29	31.75				
08	8.89	10.16	7.62	18	21.59	22.86	20.32	28	34.29	35.56	33.02				
09	10.16	11.43	8.89	19	22.86	24.13	21.59	29	35.56	36.83	34.29				
10	11.43	12.70	10.16	20	24.13	25.40	22.86	30	36.83	38.10	35.56				
11	12.70	13.97	11.43	21	25.40	26.67	24.13	31	38.10	39.37	36.83				