



- SPECIFICATIONS**
- 1、Current Rating: 1A AC, DC
 - 2、Voltage Rating: 125V AC, DC
 - 3、Temperatuer Range: $-40^{\circ}\text{C} \sim +105^{\circ}\text{C}$
 - 4、Contact Resistance: $20\text{m}\Omega$ Max
 - 5、Insulation Resistance: $100\text{M}\Omega$ Min
 - 6、Withstanding Voltang: 500V AC/minute
 - 7、Material: Phosphoric brass Tin-plated
 - 8、Applicable Wire Sizes: AWG #28~32#
Insulation O.D. = $0.5 \sim 1.0\text{mm}$

			GENERAL TOLERANCE	制图 DRAWING	05							
			DIM TOL	审核 CHECK	 深圳市华灿天禄电子有限公司 ShenzhenhuacantianluELECTRONICS CO., LTD							
			X.X ± 0.30	批准 APPROVAL					产品名称 TITLE	1.25 端子	版本 REV.	A
1	初版发行		X.XX ± 0.20	比例 SCALE					产品料号 PART NO.	HC-1.25-T	单位 UNITS	mm
序号 No.	变更内容 MODIFY CONTENT	日期 MODIFY DATE	X.XXX ± 0.10	投影 Projection		材料 MATERIAL	页次 SHEET	1/1				
			Angle $\pm 3.0^{\circ}$									