



主要参数:

1. 额定电压、电流: 125V/1.5A max
2. 接触电阻: 40mΩ Max
3. 绝缘电阻: 500MΩ Min
4. 耐压测试: DC500V/5.0mA for 1 minute
5. 盐雾测试: 8±0.5H
6. 焊接温度: 260±5°C 3±0.5s

其他要求

1. 产品应无错装。漏装零件等现象;
2. 零件表面应无裂纹、缺料、飞边等现象, 表面镀层应光亮美观
3. 未注尺寸公差为±0.15mm

| | | | | |
|----|------|------|-------|----|
| 5 | 1ED灯 | 铁针 | 黄/绿 | |
| 4 | 信号针 | 磷铜 | 镀金 | |
| 3 | 后盖 | PA66 | 黑(环保) | |
| 2 | 塑座 | PA66 | 黑(环保) | |
| 1 | 屏蔽 | 黄铜 | 镀铜锡 | |
| 序号 | 名称 | 材料 | 电镀 | 备注 |



深圳市华宇创精密电子有限公司

| | | | | |
|---|---------------------|----------------------|-------------------------------|---------------------|
| TOLERANCE: X.X ±0.30 X.XX ±0.25 X.XXX ±0.15 X' ±2' X.X' ±0.5' | DRAWN BY : 陈一鸣 | DATE : 2014-02-23 | PART NAME: R45 180° DIP带灯 | |
| | CHECKED BY: 马跃 | DATE : 2014-02-23 | PART NO. HYCW102-RJ45-385B | MOLD NO. |
| UNIT: mm [inch] SCALE:1:1 SIZE: A4 | APPROVED BY: 邱国夷 | DATE : 2014-02-23 | DRAW NO: HYC-RJ17041309 | SHEET NO. 1 OF 1 |