

## XE2NP2131

limit switch contact block - 2NO - slow-break,  
simultaneous



### Main

|                               |  |
|-------------------------------|--|
| Range of product              | OsiSense XC  |
| Series name                   | Standard format  |
| Product or component type     | Limit switch contact block                                   |
| Device short name             | XE2N   |
| Associated body               | ZCD28<br>ZCKJ8<br>ZCKJ8D<br>ZCKL8<br>ZCKM8<br>ZCKS8<br>ZCP28 |
| Number of poles               | 2  |
| Contacts type and composition | 2 NO   |
| Contacts operation            | Slow-break, simultaneous                                     |

### Complementary

|   |   |
|---|---|
| Product compatibility                               | XCKD<br>XCKJ<br>XCKL<br>XCKM<br>XCKP<br>XCKS  |
| Electrical connection                               | Screw-clamp terminals, clamping capacity: 1 x 0.5...2 x 2.5 mm <sup>2</sup>   |
| Contacts insulation form                            | Zb  |
| Contacts material                                   | Silver plated contacts  |
| Positive opening                                    | Without   |
| Minimum actuation speed                             | 6 m/min   |
| Contact code designation                            | Q300, DC-13 (U <sub>e</sub> = 250 V, I <sub>e</sub> = 0.27 A) conforming to EN/IEC 60947-5-1 appendix A<br>A300, AC-15 (U <sub>e</sub> = 240 V, I <sub>e</sub> = 3 A), I <sub>the</sub> = 10 A conforming to EN/IEC 60947-5-1 appendix A  |
| Resistance across terminals                         | < 25 mOhm conforming to IEC 60255-7 category 3  |
| [U <sub>i</sub> ] rated insulation voltage          | 500 V degree of pollution 3 conforming to IEC 60947-1<br>300 V conforming to CSA C22-2 No 14<br>300 V conforming to UL 508  |
| [U <sub>imp</sub> ] rated impulse withstand voltage | 6 kV conforming to IEC 60664<br>6 kV conforming to IEC 60947-1  |
| Short circuit protection                            | 10 A by gG cartridge fuse   |
| Electrical durability                               | 5000000 cycles, DC-13 120 V, 7 W, operating rate: < 60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C<br>5000000 cycles, DC-13 24 V, 13 W, operating rate: < 60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C<br>5000000 cycles, DC-13 48 V, 9 W, operating rate: < 60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C |

### Environment

### Offer Sustainability

|                               |   |
|-------------------------------|---|
| Sustainable offer status      | Green Premium product   |
| RoHS                          | Compliant - since 0851 - Schneider Electric declaration of conformity |
| REACH                         | Reference not containing SVHC above the threshold                     |
| Product environmental profile | Available   |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

