

REVISIONS					
REV.	ECN NO.	LOCATION	DESCRIPTION	DATE	DESIGN
A1	N/A		图面升级整理图面	2025.07.01	阿树
A2	ECN-P-2026052706	Ⓐ2 X6	产品材质及尺寸变更	2026.05.27	山楂

Specifications:
规格:
1.Voltage rating:30VAC/DC
额定电压: 30V AC/DC
2.Current rating:3A AC/DC
额定电流: 3A AC/DC
3.Withstanding voltage:500V AC/minute
耐受电压: ≥500V AC/分钟
4.Temperature range: -30℃-+70℃
温度范围: -30℃-+70℃
5.Insulation resistance:100MΩMIN
绝缘电阻: ≥100MΩ
6.Contact resistance:30mΩMax
接触电阻: ≥30mΩ
7.Life:5000 cycles
寿命: 5000次
8.Insertion and extrscion force: 3-20N
插拔力: 3-20N

SCHEMATIC	
Model	DC-0360
Center Pin	Ø1.65 mm
	Ø2.0 mm
	Ø2.5 mm

Ⓐ2	5	Center pin	1	H62 Brass rods	-	Tin bronze
	4	plain film	1	H62 Brass rods	T=0.30	Silver
	3	illustration	1	H62 Brass rods	T=0.30	Silver
	2	Contact	1	H65	T=0.30	Silver
	1	Pedestal	1	PPA	Black	-
	ITEN	Name	Number	Material	Color	PLATING

AuGLAR	±5°
X.	±0.40
X.x	±0.30
X.xx	±0.20
X.xxx	±0.15
UNSPECIFIED TOLERAuces	



DESIGN	山楂	VIEW:		MODEL TYPE:	DC POWER JACK
CHECKED		UNIT:	mm/in	PART NO.:	DC-0360-2.5
APPROVED		SIZE:	A4	DWG NO.:	

SCALE	PAGE	REVISION
N/A	1/1	A2

A

A

B

B

C

C

D

D

1

2

3

4