

G2-LAURA-R-XW-P

Mini reflector with ~72° wide beam. Assembly with thinner white holder, installation tape and location pins.


TECHNICAL SPECIFICATIONS:

Dimensions	21.6 mm
Height	13.1 mm
Fastening	tape, pin
Colour	white
Box size	451 x 254 x 152 mm
Box weight	3.4 kg
Quantity in Box	1440 pcs
ROHS compliant	yes ⓘ



MATERIAL SPECIFICATIONS:



Component	Type	Material	Colour
LAURA-R-XW	Reflector	HRPC	white
LAURA-LT-PIN-XP-HLD-WHT	Holder	PC	
ROSE-TAPE	Tape	PU tape	





PHOTOMETRIC DATA (MEASURED):




LED XP-E
FWHM 71.0°
Efficiency 84 %
Peak intensity 0.700 cd/lm
LEDs/each optic 1
Light colour White
Required components:





LED XP-E2
FWHM 74.0°
Efficiency 86 %
Peak intensity 0.630 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED XP-G
FWHM 72.0°
Efficiency 86 %
Peak intensity 0.590 cd/lm
LEDs/each optic 1
Light colour White
Required components:





LED XP-G2
FWHM 71.0°
Efficiency 87 %
Peak intensity 0.760 cd/lm
LEDs/each optic 1
Light colour White
Required components:





PHOTOMETRIC DATA (MEASURED):





LED XT-E
FWHM 74.0°
Efficiency 86 %
Peak intensity 0.640 cd/lm
LEDs/each optic 1
Light colour White
Required components:





LED LUXEON 3030 2D (Round LES)
FWHM 70.0°
Efficiency 83 %
Peak intensity 0.710 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED LUXEON TX
FWHM 71.0°
Efficiency 82 %
Peak intensity 0.680 cd/lm
LEDs/each optic 1
Light colour White
Required components:





LED NCSxx19A
FWHM 74.0°
Efficiency 83 %
Peak intensity 0.580 cd/lm
LEDs/each optic 1
Light colour White
Required components:




PHOTOMETRIC DATA (MEASURED):





LED NVSxx19A
FWHM 75.0°
Efficiency 81 %
Peak intensity 0.560 cd/lm
LEDs/each optic 1
Light colour White
Required components:




LED NVSxx19B/NVSxx19C
FWHM 70.0°
Efficiency 79 %
Peak intensity 0.700 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED OSOLON Square EC
FWHM 70.0°
Efficiency 84 %
Peak intensity 0.720 cd/lm
LEDs/each optic 1
Light colour White
Required components:



PHOTOMETRIC DATA (SIMULATED):



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)