

REVISIONS					
REV.	ECN NO.	LOCATION	DESCRIPTION	DATE	DESIGN
A0	N/A		INITIAL RELEASE	/	/
A1	N/A		图面升级整理图面	2024.12.9	阿树

Specifications:
规格:
Voltage rating:50V AC/DC
额定电压: 50V AC/DC
Current rating:1A AC/DC
额定电流: 1A AC/DC
Withstanding voltage:250V
AC/minute
耐受电压: 250V AC/分钟
Temperature range:-25℃--+85℃
温度范围: -25℃--+85℃
Insulation resistance:≥100MΩ
绝缘电阻: ≥100MΩ
Contact resistance:≤20mΩ
接触电阻: ≤20mΩ

PART NO.:

X1004 I-P V01
① ② ③ ④

- ①Series No
②Category:T-Terminal
③Material:P-Phosphor Bronze
④Plating:SN-Bright Tin Plating
100u"Min,Nickel 50u"Min
V01-Contact Area Gold Flash.
Other Area:Gold Flash,Ni:50u"Min

X1004T-PSN	Phosphor Bronze	AWG#28-32 O.D:0.8mm	X1004W	X1004H
X1004T-PV01				
PART NO	Material	Wire Range	Suitable XKBSuitable Wafer	XKB Housing

AuGLAR	±5°
X.	±0.40
X.x	±0.30
X.xx	±0.20
X.xxx	±0.15
UNSPECIFIED TOLERANCES	



DESIGN	阿树	VIEW:		MODEL TYPE: 1.0mm Crimp Style Connector
CHECKED		UNIT:	mm/in	PART NO.: X1004T-PV01
APPROVED		SIZE:	A4	DWG NO.: X-X1004T-PV01

SCALE	PAGE	REVISION
N/A	1/1	A1

