

Pitch:5.08mm(0.20 ")
Board Spacer Single Row Straight Type

ELETE
—Professional Connecting Solution—
HMRSSH25 Series


Specifications

Current Rating:7.9 Ampere
Insulation Resistance:1000MΩ Min
Dielectric Withstanding:1500V AC
Contact Resistance:20mΩ Max
Operating Temperature:-40℃ to +105℃



Materials

Contact Material: Brass
Insulation Material: Polyester,UL 94V-0
LCP/NL6T





All material RoHS&Reach Compliant
Halogen-free is available



Mating with



HFRSS89



No. of Pins/Row	Dimension Information		No. of Pins/Row	Dimension Information		No. of Pins/Row	Dimension Information		No. of Pins/Row	Dimension Information	
	D	E		D	E		D	E		D	E
02	10.16	5.08	08	40.64	35.56	14	71.12	66.04	20	101.60	96.52
03	15.24	10.16	09	45.72	40.64	15	76.20	71.12			
04	20.32	15.24	10	50.80	45.72	16	81.28	76.20			
05	25.40	20.32	11	55.88	50.80	17	86.36	81.28			
06	30.48	25.40	12	60.96	55.88	18	91.44	86.36			
07	35.56	30.48	13	66.04	60.96	19	96.52	91.44			