




Series
NSX

SIZE 16 CRIMP REMOVABLE PIN CONTACT

Issue:
JANUARY 25 2002

Page
1 / 1



MATERIAL AND FINISH :
COPPER ALLOY - GOLD OVER NICKEL

WIRES ACCOMMODATED : AWG 16-18-20
INSULATION DIAMETER : .130 MAX
STRIP LENGTH : .236

TOOLING
CRIMPING TOOL : M22520/1-01 RADIAL 282 291
SELECTOR POSITION : 6 FOR AWG 16
5 FOR AWG 18
4 FOR AWG 20

POSITIONER : M22520/1-02 RADIAL 282 972
INSERTION AND EXTRACTION TOOL : M81969/1-03 RADIAL 282 546

CREATION				
PEN: .				
NOM: L FALETTI	JAN 25 02	ADD ZONE MARKING 'S'	COUTHON	GOMBERT
DATE: 27 APR 83	12 APR 96	SELECTOR POSITION MODIFIED	VALGRESY	BALDYROU
APPR.:	05 APR 96	DIMENSIONS MODIFIED ACCORDING TO ARINC 600	VALGRESY	BALDYROU
	Issue	Revisions	Name	Approved

A620230

This information is given as an indication. In the continual goal to improve our products, we reserve the right to make any modifications judged necessary.

4112-9311