







REVISIONS					
REV.	ECN NO.	LOCATION	DESCRIPTION	DATE	DESIGN
A1	N/A			2025.06.28	
A2	N/A	A2X5		2025.11.25	



- SPECIFICATION
- 1.Rating DC 20V 1A
 - 2.Contact resistance $\leq 30\Omega$
 - 3.Insulation resistance $\geq 100M\Omega$ (DC250V)
 - 4.Withstand voltage 500VAC
 - 5.Insertion and extraction force 3-20N;
 - 6.life test 5,000 cycles



Plastic	PA9T	Black
Terminal 8	Phosphor Bronze	Gold
Terminal 7	Phosphor Bronze	Gold
Terminal 6	Phosphor Bronze	Gold
Terminal 5	Phosphor Bronze	Gold
Terminal 4	Phosphor Bronze	Gold
Terminal 3	Phosphor Bronze	Gold
Terminal 2	Phosphor Bronze	Gold
Terminal 1	Phosphor Bronze	Gold
PAPT NAMF	MATERIAL	PLATING

T:1.6 DIMENSIONS OF DC BOARD HOLES
TOLERANCES:±0.10(PRINTED-TOP VIEW)

AuGLAR	±5°
X.	±0.40
X.x	±0.30
X.xx	±0.20
X.xxx	±0.15
UNSPECIFIED TOLERANCES	



DESIGN	VIEW:	MODEL TYPE: 3.5 PHONE JACK
CHECKED	UNIT: mm/in	PART NO.: PJ-35374
APPROVED	SIZE: A4	DWG NO.: