

1

2

3

4

A

A

B

B


C

C

D

D

REVISIONS					
REV.	ECN NO.	LOCATION	DESCRIPTION	DATE	DESIGN
A0	N/A		INITIAL RELEASE	/	/
A1	N/A		图面升级整理图面	2025.06.26	阿树

Model No.	PJ-326-SMT
Schematic	

Technical characteristics

技术特征

Service condition: $-30 \sim 70^{\circ}$ 使用条件: $-30 \sim 70^{\circ}$

Rated load: DC30V 0.5A

额定负载: DC30V 0.5A

Contact resistance: $\leq 0.03 \Omega$ 接触电阻: $\leq 0.03 \Omega$ Insulation resistance: $\geq 100M\Omega$ DC250V绝缘电阻: $\geq 100M\Omega$ DC250V

Pressure: AC500V(50HZ)/min

压力: AC 500v(50HZ)/分钟

Insertion and pulling force: 3~20N

插拔力: 3~20N

Life expectancy: 5000

寿命: 5000

Plastic	PPA	
Terminal 3	Phosphor Bronze	TIN
Terminal 2	Phosphor Bronze	TIN
Terminal 1	Phosphor Bronze	TIN
PAPT NAMF	MATERIAL	PLATING

AuGLAR	$\pm 5^{\circ}$
X.	± 0.40
X.x	± 0.30
X.xx	± 0.20
X.xxx	± 0.15
UNSPECIFIED TOLERANCES	



DESIGN	阿树	VIEW:		MODEL TYPE:	3.5 PHONE JACK
CHECKED		UNIT:	mm/in	PART NO.:	PJ-326-SMT
APPROVED		SIZE:	A4	DWG NO.:	X-PJ-326-SMT

SCALE	PAGE	REVISION
N/A	1/1	A1

