

CMD65R660S6ZD/CMU65R660S6ZD

650V, 600mΩ typ., 6A N-Channel Super Junction Power MOSFET

General Description

The 65R660S6ZD is power MOSFET using Cmos's advanced super junction technology that can realize very low on resistance , gate charge and reduced tendency for ringing. As a result, its switching loss is very low, making it optimized for switching applications. Moreover, these user friendly devices offer the advantages of improved ruggedness and remarkable ESD capability by integrated Zener diode, making it an ideal choice for designers.

Features

- Multi-layer Epitaxial Chip Technology
- Low On-Resistance
- 100% avalanche tested
- RoHS Compliant


Product Summary

BVDSS	R _{DS(on)} max.	ID
650V	0.66Ω	6A

Applications

- Adapter
- PFC power supply stages
- DC-DC converters

TO-252/251 Pin Configuration



Absolute Maximum Ratings

Symbol	Parameter	Rating	Units
V _{DS}	Drain-Source Voltage	600	V
V _{GS}	Gate-Source Voltage	±25	V
I _D @T _C =25°C	Continuous Drain Current	6	A
I _D @T _C =100°C	Continuous Drain Current	3.8	A
I _{DM}	Pulsed Drain Current	24	A
EAS	Single Pulse Avalanche Energy ¹	21	mJ
P _D @T _C =25°C	Total Power Dissipation	75	W
T _{STG}	Storage Temperature Range	-55 to 150	°C
T _J	Operating Junction Temperature Range	-55 to 150	°C

Thermal Data

Symbol	Parameter	Typ.	Max.	Unit
R _{θJA}	Thermal Resistance Junction-ambient	---	40.6	°C/W
R _{θJC}	Thermal Resistance Junction-case	---	1.67	°C/W

CMD65R660S6ZD/CMU65R660S6ZD

650V, 600mΩ typ., 6A N-Channel Super Junction Power MOSFET

Electrical Characteristics(T_J=25°C, unless otherwise noted)

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V, I _D =250uA	650	---	---	V
R _{DS(ON)}	Static Drain-Source On-Resistance	V _{GS} =10V, I _D =4A	---	600	660	mΩ
V _{GS(th)}	Gate Threshold Voltage	V _{GS} =V _{DS} , I _D =250uA	2.5	---	4.5	V
I _{DSS}	Drain-Source Leakage Current	V _{DS} =650V, V _{GS} =0V	---	---	1	μA
I _{GSS}	Gate-Source Leakage Current	V _{GS} =±25V, V _{DS} =0V	---	---	±10	μA
g _{fs}	Forward Transconductance	V _{DS} =30V, I _D =4A	---	3.8	---	S
R _g	Gate Resistance	V _{DS} =0V, V _{GS} =0V, f=1MHz	---	12	---	Ω
Q _g	Total Gate Charge	I _D =1.7A	---	12	---	nC
Q _{gs}	Gate-Source Charge	V _{DD} =400V	---	2.5	---	
Q _{gd}	Gate-Drain Charge	V _{GS} =10V	---	6	---	
T _{d(on)}	Turn-On Delay Time	V _{DD} =325V V _{GS} =10V R _G =25Ω, I _D =6A	---	15	---	ns
T _r	Rise Time		---	21	---	
T _{d(off)}	Turn-Off Delay Time		---	45	---	
T _f	Fall Time		---	10	---	
C _{iss}	Input Capacitance	V _{DS} =100V, V _{GS} =0V, f=1MHz	---	450	---	pF
C _{oss}	Output Capacitance		---	23	---	
C _{rss}	Reverse Transfer Capacitance		---	2	---	

Diode Characteristics

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
I _S	Continuous Source Current	V _G =V _D =0V, Force Current	---	---	6	A
I _{SM}	Pulsed Source Current		---	---	24	A
V _{SD}	Diode Forward Voltage	V _{GS} =0V, I _S =6A	---	0.89	1.4	V
t _{rr}	Reverse Recovery Time	I _S =1.7A, V _{DD} =400V	---	146	---	ns
Q _{rr}	Reverse Recovery Charge	di/dt=100A/μs	---	0.6	---	μC

Note :

1.The EAS data shows Max. rating . The test condition is V_{DD}=100V, V_{GS}=10V, L=30mH, I_{AS}=1.2A.

This product has been designed and qualified for the consumer market.







Cmos assumes no liability for customers' product design or applications.

Cmos reserves the right to improve product design, functions and reliability without notice. Please refer to the latest version of specification.

CMD65R660S6ZD/CMU65R660S6ZD

650V, 600mΩ typ., 6A N-Channel Super Junction Power MOSFET


Typical Characteristics



Package Dimension

TO-252

Unit :mm



CMD65R660S6ZD/CMU65R660S6ZD

650V, 600mΩ typ., 6A N-Channel Super Junction Power MOSFET

Package Dimension

TO-251A

Unit :mm

